


Flange Insulation: SPECIAL APPLICATION

Jock Gasket Only

Type "E" (Full Face) and Type "F" (Ring Gasket)

Gasket: Phenolic with Viton® Seal, G3 with Viton® Seal or G10 with Viton®



Pipe Size	TYPE "E" GASKET						TYPE "F" GASKET					
	150 Class	300 Class	400 Class	600 Class	900 Class	1500 Class	150 Class	300 Class	400 Class	600 Class	900 Class	1500 Class
2"	•	•	•	•	•	•	•	•	•	•	•	•
2½"	•	•	•	•	•	•	•	•	•	•	•	•
3"	•	•	•	•	•	•	•	•	•	•	•	•
3½"	•	•	•	•	•	•	•	•	•	•	•	•
4"	•	•	•	•	•	•	•	•	•	•	•	•
5"	•	•	•	•	•	•	•	•	•	•	•	•
6"	•	•	•	•	•	•	•	•	•	•	•	•
8"	•	•	•	•	•	•	•	•	•	•	•	•
10"	•	•	•	•	•	•	•	•	•	•	•	•
12"	•	•	•	•	•	•	•	•	•	•	•	•
14"	•	•	•	•	•	•	•	•	•	•	•	•
16"	•	•	•	•	•	•	•	•	•	•	•	•
18"	•	•	•	•	•	•	•	•	•	•	•	•
20"	•	•	•	•	•	•	•	•	•	•	•	•
22"	•	•	•	•	•	•	•	•	•	•	•	•
24"	•	•	•	•	•	•	•	•	•	•	•	•
26"	•	•	•	•	•	•	•	•	•	•	•	•
28"	•	•	•	•	•	•	•	•	•	•	•	•
30"	•	•	•	•	•	•	•	•	•	•	•	•
32"	•	•	•	•	•	•	•	•	•	•	•	•
34"	•	•	•	•	•	•	•	•	•	•	•	•
36"	•	•	•	•	•	•	•	•	•	•	•	•

Larger sizes and high temperature sets (G3, G7 & G10) available on request.

Unless otherwise specified, all kits will be shipped with one (1) full length Mylar® sleeve, two (2) phenolic washers, and two (2) steel washers per bolt.