

## STAC Coating System: STACwrap



### STACwrap SPECIFICATIONS

Tensile Strength	45 lbf/in min	(200 N/25mm)
Water Vapor Permeability	0.006 Perms avg.	(ASTM E96-66 A)
Breakdown Voltage	16 Kv min with 55% overlap	
Mass	0.295 lb/ft <sup>2</sup> avg	(1.44 kg/m <sup>2</sup> avg)
Application Temperature Range	23°F to 165°F	(-5°C to 55°C)
Service Temperature Range	-270°F to 180°F	(-168°C to 80°C)
Thickness	>40 mils	(>1.0 mm avg)
Length	33 ft roll	(10 m roll)
Standard Widths	2" to 12"	(50 mm to 300 mm)
Packaging	72" × 33'/case	(18 m <sup>2</sup> /case)

### STACwrap Coating System

Part Number	Product	Description	Weight
5810004	STACwrap 2"	36 Rolls @ 33' each / per case	62.00
5810005	STACwrap 3"	24 Rolls @ 33' each / per case	61.00
5810006	STACwrap 4"	18 Rolls @ 33' each / per case	59.00
5810007	STACwrap 6"	12 Rolls @ 33' each / per case	56.00
5810008	STACwrap 8"	8 Rolls @ 33' each / per case	51.00
5810009	STACwrap 12"	6 Rolls @ 33' each / per case	63.00