

Electrofusion Fittings: Couplings

NOTE: Operating Pressure is 200 psi for PE4710 Couplings in allowable applications.

(PE3408/PE4710) ELECTROFUSION COUPLINGS

| Size | Description | Pin Type | Part Number | Pack. Qty. | Wt. | AWWA |
|------------|------------------------|----------|-------------|------------|-------|------|
| ½" CTS | ASTM D2513/F1055 | 4.7 R | 5760019 | 50 | 0.09 | YES |
| ¾" CTS | ASTM D2513/F1055 | 4.7 R | 10004578 | 40 | 0.10 | YES |
| 1" CTS | ASTM D2513/F1055 | 4.7 R | 5760023 | 25 | 0.18 | YES |
| 1¼" CTS | ASTM D2513/F1055 | 4.7 R | 10004573 | 30 | 0.16 | YES |
| 2" CTS | ASTM D2513/F1055 | 4.7 S | 10004580 | 30 | 0.46 | - |
| ½" IPS | ASTM D2513/F1055 | 4.7 R | 10004627 | 40 | 0.13 | YES |
| ¾" IPS | ASTM D2513/F1055 | 4.7 R | 5760022 | 25 | 0.29 | YES |
| 1" IPS | ASTM D2513/F1055 | 4.7 R | 5760024 | 25 | 0.14 | YES |
| 1¼" IPS | ASTM D2513/F1055 | 4.7 R | 5760026 | 50 | 0.28 | YES |
| 1½" IPS | ASTM D2513/F1055 | 4.7 R | 5760028 | 35 | 0.34 | YES |
| 2" IPS | ASTM D2513/F1055 | 4.7 R | 5760030 | 25 | 0.38 | YES |
| 2½" IPS | CONDUIT PSI=0 | 3 Pin | call | 20 | 0.55 | - |
| 3" IPS | ASTM D2513/F1055 | 4.7 R | 10000358 | 36 | 1.57 | YES |
| 4" IPS | ASTM D2513/F1055 | 4.7 R | 10000360 | 10 | 1.67 | YES |
| 6" IPS | ASTM D2513/F1055 | 4.7 R | 10000359 | 8 | 4.37 | YES |
| 7" IPS | ASTM F1055 | 4.7 S | 10003970 | 4 | 7.86 | - |
| 8" IPS | ASTM D2513/F1055 | 4.7 R | 10000361 | 4 | 8.43 | YES |
| 10" IPS | ASTM D2513/F1055 | 4.7 R | 10004579 | 1 | 15.40 | YES |
| 10" IPS ** | ASTM D2513/F1055 | 4.7 S | 10000362 | 1 | 15.24 | YES |
| 12" IPS | ASTM D2513/F1055 | 4.7 R | 10004571 | 1 | 23.10 | YES |
| 12" IPS ** | ASTM D2513/F1055 | 4.7 S | 10000363 | 1 | 23.90 | YES |
| 1¼" SIDR 7 | 1.488 OD CONDUIT PSI=0 | 4.7 R | 10004575 | 40 | 0.29 | - |
| 1¼" SIDR 9 | 1.580 OD CONDUIT PSI=0 | 4.7 R | 10004577 | 30 | 0.24 | - |
| 4" DIPS | ASTM D2513/ F1055 | 4.7 S | 10000353 | 10 | 2.34 | YES |
| 6" DIPS | ASTM D2513/ F1055 | 4.7 S | 10000354 | 8 | 4.59 | YES |
| 8" DIPS | ASTM D2513/ F1055 | 4.7 S | 10000355 | 4 | 8.37 | YES |
| 10" DIPS | ASTM D2513/ F1055 | 4.7 S | 10000356 | 1 | 17.43 | YES |
| 12" DIPS | ASTM D2513/F1055 | 4.7 S | 10000357 | 1 | 25.67 | YES |

Call for availability of other sizes and dimensions.

** For Use with Bar-Code Processor Only

4.7R = 4.7 Pin with Resistor

4.7S = 4.7 Solid Pin