

MODEL


# C726 Y - STRAINER FOR COPPER TUBING (CTS)

The **Shurjoint** C726 Y-Strainer can be installed quickly and easily with two mechanical couplings and the straight flow through design provides for lower pressure drop.

### Pressure-Temperature Rating

Nom. Ratings	Working Pressure (Type K Copper Tubing)	Shell Test (Hydrostatic)	Max. Service Temperature
Class 150	300 psi @100°F 20 Bar @38°C	450 psi 32 Bar	EPDM: 230°F / 110°C

\*Working pressure is for connection with roll-grooved Type K copper tubing.  
\*Proof test pressure: 1.5 times the working pressure.  
\*Burst pressure: 3 times the listed working pressure, min.



Nominal Size mm / in	Pipe O. D. mm / in	Max. Working Pressure Bar / PSI	Dimensions			Drain Plug Size mm / in	Approx. Weight Kgs / Lbs
			A mm / in	B mm / in	C mm / in		
50	54.0	20	222	162	81	15	4.0
2	2.125	300	8.75	6.38	3.18	½	8.8
65	66.7	20	248	170	96	15	5.1
2½	2.625	300	9.75	6.69	3.78	½	11.3
80	79.4	20	270	196	114	15	6.8
3	3.125	300	10.63	7.71	4.50	½	15.0
100	104.8	20	330	244	152	25	12.5
4	4.125	300	13.00	9.60	6.00	1	27.5
150	155.6	20	432	328	203	25	26.9
6	6.125	300	17.00	12.91	8.00	1	59.3