

GTS COPPER FITTINGS

CTS Copper Fittings are produced with groove and cup ends in a variety of fitting configurations. The fittings are constructed to ASTM B75 UNS C12200 with minimum copper content of 99.9%. Fitting pressure ratings match the ratings of the Figure 6400 Coupling.




FIG. 6050




FIG. 6051




FIG. 6060




FIG. 6074

DIMENSIONS/WEIGHTS — ELBOWS, TEES & CAPS

Nominal Size	Copper Tube Diameter	Fig. 6050 90° Elbow		Fig. 6051 45° Elbow		Fig. 6060 Tee		Fig. 6074 Cap	
		C to E	Wt. Ea.	C to E	Wt. Ea.	C to E	Wt. Ea.	E to E	Wt. Ea.
<i>In.</i>	<i>In./mm</i>	<i>In./mm</i>	<i>Lbs./kg</i>	<i>In./mm</i>	<i>Lbs./kg</i>	<i>In./mm</i>	<i>Lbs./kg</i>	<i>In./mm</i>	<i>Lbs./kg</i>
2	2.125 54.0	2.91 74	0.75 0.34	2.19 56	0.61 0.28	2.69 68	1.45 0.66	2.00 51	0.36 0.16
2½	2.625 66.7	3.31 84	1.15 0.52	2.31 59	0.89 0.40	3.20 81	2.37 1.07	2.00 51	0.50 0.23
3	3.125 79.4	3.81 97	1.88 0.85	2.59 66	1.38 0.63	3.52 89	3.38 1.53	2.00 51	0.69 0.31
4	4.125 104.8	4.75 121	4.07 1.85	3.19 81	2.99 1.36	4.25 108	5.77 2.62	2.00 51	1.15 0.52
5	5.125 130.2	5.94 151	6.94 3.15	3.25 83	4.00 1.81	5.94 151	12.84 5.82	2.75 70	1.81 0.82
6	6.125 155.6	6.94 176	11.12 5.04	3.63 92	6.16 2.79	6.94 176	21.00 9.52	3.13 80	2.68 1.22
8	8.125 206.4	7.75 197	21.81 9.89	4.25 108	13.66 6.20	7.75 197	21.81 9.89	— —	— —