


## AWWA Ductile Iron Series

**Shurjoint** offers a variety of grooved mechanical couplings and fittings for AWWA ductile iron pipe in sizes 3" to 24". The **Shurjoint** coupling features a two-piece housing and GapSeal® gasket for a leak-tight seal. Ductile iron pipe shall be cut-grooved to AWWA C-606 Table 2 and Table 3 - Radius Cut Groove Specifications.

Rubber gaskets are specially compounded to seal on ductile iron surfaces and are available in three grades to meet your service requirement needs. See page 131 for details.



### Radius Cut Groove Specification For Ductile Iron Pipe



#### Gasket Seating Surface (Column 3)

The same coupling can be used either as a rigid joint or a flexible joint depending on the groove. Gasket seat "A Rigid" is for rigid joints and Gasket seat "A Flex." for flexible joints.

The gasket seating surface shall be free from deep scores, marks, or ridges that could prevent a positive seal.

#### Groove Diameter (Column 5)

The 'C' diameters are average values. The groove must be of uniform depth around the entire pipe circumference.

#### Radius (Column 6)

The groove must be cut with a radius "R" at the corners of the groove to reduce stress concentration.

#### Minimum Wall Thickness (Column 7)

"T" is the minimum allowable wall thickness that may be cut-grooved; tolerances are to conform to ANSI /AWWA C151/A21.51.

### AWWA Ductile Iron Pipe

Nominal Size mm / in	Pipe O. D.				Gasket Seat A		Groove Width B mm / in	Groove Dia. C		Radius R mm / in	Min. Allow Wall Thick T mm / in
	Basic mm / in	Tolerance			Rigid mm / in	Flex. mm / in		Basic mm / in	Tol. +0 mm / in		
		+ mm / in	- mm / in		+0/-0.51 +0/-0.02	+0.41/-1.19 +0.016/-0.047			+0 mm / in		
80	100.6	+1.14	-1.14		21.34	19.05	9.53	94.56	-0.51	3.05	7.9
3	3.96	+0.045	-0.045		0.840	0.750	0.375	3.723	-0.020	0.120	0.31
100	121.9	+1.14	-1.14		21.34	19.05	9.53	115.90	-0.51	3.05	8.1
4	4.80	+0.045	-0.045		0.840	0.750	0.375	4.563	-0.020	0.120	0.32
150	175.3	+1.52	-1.52		21.34	19.05	9.53	169.06	-0.51	3.05	8.6
6	6.90	+0.060	-0.060		0.840	0.750	0.375	6.656	-0.020	0.120	0.34
200	229.9	+1.52	-1.52		24.13	22.23	12.70	223.04	-0.64	3.68	9.1
8	9.05	+0.060	-0.060		0.950	0.875	0.500	8.781	-0.025	0.145	0.36
250	281.9	+1.52	-1.52		25.78	23.83	12.70	274.65	-0.64	3.68	9.7
10	11.10	+0.060	-0.060		1.015	0.938	0.500	10.813	-0.025	0.145	0.38
300	335.3	+1.52	-1.52		25.78	23.83	12.70	327.81	-0.76	3.68	10.2
12	13.20	+0.060	-0.060		1.015	0.938	0.500	12.906	-0.030	0.145	0.40
350	388.6	+1.27	-2.03		25.78	23.83	15.88	327.81	-0.76	4.19	10.7
14	15.30	+0.050	-0.080		1.015	0.938	0.625	14.969	-0.030	0.165	0.42
400	442.0	+1.27	-2.03		34.04	30.18	15.88	433.40	-0.76	4.19	10.9
16	17.40	+0.050	-0.080		1.340	1.188	0.625	17.063	-0.030	0.165	0.43
450	495.3	+1.27	-2.03		34.04	30.18	15.88	485.78	-0.76	4.70	11.2
18	19.50	+0.050	-0.080		1.340	1.188	0.625	19.125	-0.030	0.185	0.44
500	548.6	+1.27	-2.03		34.04	30.18	15.88	538.96	-0.76	4.70	11.4
20	21.60	+0.050	-0.080		1.340	1.188	0.625	21.219	-0.030	0.185	0.45
600	655.3	+1.27	-2.03		34.04	30.18	15.88	645.31	-0.76	4.70	11.9
24	25.80	+0.050	-0.080		1.340	1.188	0.625	25.046	-0.030	0.185	0.47