

Flange Kit Weights: Type E (Full Face) and Type F (Ring)

Single Washer and Double Washer Kits

TYPE F GASKET KIT WEIGHTS

| | SINGLE WASHER KITS | | | DOUBLE WASHER KITS | | |
|-----|--------------------|------|-------|--------------------|-------|-------|
| | 150# | 300# | 600# | 150 # | 300# | 600# |
| 1" | 0.26 | 0.28 | 0.32 | 0.34 | 0.38 | 0.48 |
| 2" | 0.36 | 0.54 | 0.54 | 0.46 | 1.18 | 1.20 |
| 2½" | 0.36 | 0.82 | 0.86 | 0.48 | 1.20 | 1.35 |
| 3" | 0.40 | 0.92 | 0.92 | 0.50 | 1.28 | 1.48 |
| 4" | 0.78 | 0.96 | 1.02 | 1.08 | 1.34 | 1.82 |
| 6" | 1.00 | 1.56 | 2.26 | 1.38 | 1.76 | 3.52 |
| 8" | 1.26 | 1.96 | 2.84 | 1.64 | 2.88 | 4.24 |
| 10" | 2.00 | 3.08 | 5.54 | 3.20 | 4.64 | 8.56 |
| 12" | 3.04 | 4.98 | 6.86 | 4.08 | 6.30 | 10.26 |
| 14" | | | | 4.42 | 8.30 | 11.08 |
| 16" | 3.92 | 6.60 | 11.06 | 5.82 | 9.92 | 16.70 |
| 18" | 4.10 | | 8.86 | 6.20 | | |
| 20" | 6.48 | | 10.36 | 8.36 | 13.30 | 15.32 |
| 24" | | | 14.28 | 12.00 | 20.70 | 21.27 |

TYPE E GASKET KIT WEIGHTS

| | SINGLE WASHER KITS | | | DOUBLE WASHER KITS | | |
|-----|--------------------|-------|-------|--------------------|-------|-------|
| | 150# | 300# | 600# | 150# | 300# | 600# |
| 1" | 0.32 | 0.34 | 0.36 | 0.38 | 0.45 | 0.55 |
| 2" | 0.40 | 0.56 | 0.76 | 0.58 | | 1.02 |
| 2½" | 0.60 | 0.98 | 1.02 | 0.74 | 1.36 | |
| 3" | 0.62 | 0.98 | 1.04 | 0.76 | 1.44 | 1.48 |
| 4" | 0.84 | 1.36 | 2.26 | 1.20 | 1.92 | 2.44 |
| 6" | 1.24 | 1.78 | | 1.76 | 2.42 | 4.24 |
| 8" | 1.60 | 2.32 | 4.16 | 2.18 | 4.06 | 5.90 |
| 10" | 3.00 | 4.22 | 5.82 | 4.04 | 5.52 | 9.52 |
| 12" | | 5.14 | 7.16 | 4.44 | 7.18 | 10.26 |
| 14" | 4.20 | | | 4.84 | 10.10 | 15.60 |
| 16" | 5.64 | 8.76 | 11.58 | 7.76 | 11.40 | 17.46 |
| 18" | 6.36 | | | 8.68 | 15.46 | |
| 20" | 7.24 | 11.26 | 12.68 | 10.12 | 15.24 | 17.46 |
| 24" | 9.84 | 12.28 | | 13.56 | | |

Larger sizes, high temperature sets, and custom builds available on request. Unless otherwise specified, all kits will be shipped with one (1) full length Mylar® sleeve, two (2) phenolic washers, and two (2) steel washers per bolt.