

WATER GAUGES 20-400/410, 20-700/710 SERIES

Water Gauges & Accessories 20-400/20-410 Series

Side Mounted Handwheel Water Gauges

Side-mounted handwheels allow water gauge operation in hard-to-reach places; with all the 20 Series design features.

FEATURES

- Ideal for concealed jacketed type boilers
- No guard rod brackets: 20-405, 20-406, 20-410
- Brackets and guard rods standard: 20-407, 20-408
- EPDM standard gauge glass gasket
- Compact - requires minimum space
- Standard 1/4" needle drain valve
- Rated: 125 psig @ 350°F, 300 psig @ 100°F (See note!)
- 1-1/4" Extended shank length; 20-410
- CRN Registered



Part Number	Side	Pipe Size (in.)	Glass O.D. & Length	Wt./100 (lbs.)	Shank Length (in.)	Wheel Type
20-405-00	RH	1/2	5/8 x 12	165	.69	ALUMINUM
20-406-00	LH	1/2	5/8 x 12	165	.69	ALUMINUM
20-407-00	RH	1/2	5/8 x 12	170	.69	ALUMINUM
20-408-00	LH	1/2	5/8 x 12	170	.69	ALUMINUM
20-410-00	LH	1/2	5/8 x 12	180	1.25	ALUMINUM

Note: Service ratings are subject to pressure/temperature ratings of gauge glass and glass gaskets.

20-700/20-710 Series

Simple Expansion Tank Gauges

Available with 3/8" or 1/2" MNPT connections; EPDM gauge glass gaskets and 1/4" needle drain valve in lower arm are both standard.

FEATURES

- 20-710 has plug in top arm to insert glass straight through
- 1/4" pet cock or Apollo® ball valve optional
- Ball checks on request (20-704 only)
- Rated: 125 psig @ 350°F, 300 psig @ 100°F (See note!)
- CRN Registered



Model Number	Pipe Size (in.)	Glass O.D. & Length	Wt./100 (lbs.)
20-703-00	3/8	5/8 x 10	120
20-704-00	1/2	5/8 x 12	135

Note: Service ratings are subject to pressure/temperature ratings of gauge glass and glass gaskets.

* Not for use on boiler systems