

# HYDRONIC HEATING 35, 35-6A3/6H3 SERIES

## Hydronic Heating Specialties FF (35) Series

### All Bronze Feed Water Pressure Regulators

Available in 1/2" union threaded, threaded and solder union configurations. Purge lever/fast fill feature. Cartridge replaceable in-line.

#### FEATURES

- No cage screws
- Factory pre-set to 15 psig - adjustable 10 to 25 psig
- Temperatures to 210°F
- High capacity
- SS strainer, in-line, standard
- Choice of inlet connections



Part Number	Size (in.)	Height (in.)	Length (in.)	Wt./100 (lbs.)
35-503-01	1/2 Union Threaded	5.25	4.31	255
35-603-01	1/2 Threaded	5.25	3.50	225
35-703-01	1/2 Solder Union	5.25	3.18	232


## Hydronic Heating Specialties FFB (35-6A3/6H3) Series

### All Bronze Combination Backflow Preventer & Feed Water Regulators

Positive protection against backflow when supply pressure falls below system pressure.

#### FEATURES

- Suitable for hot water service
- Designed for continuous pressure, hot or cold water service
- Built-in strainer
- Max pressure 175 psig
- Max temp 250°F
- Backflow device is ASSE and CSA listed



Part Number	Size (in.)	Height (in.)	Length (in.)	Wt./100 (lbs.)
35-6A3-BF	1/2 Union NPT x NPT	5.25	8.50	450
35-6H3-BF	1/2 Solder Union x NPT	5.25	8.50	440
35-6A3-BFC*	1/2 Union NPT x NPT	5.25	8.50	450
35-6H3-BFC*	1/2 Solder Union x NPT	5.25	8.50	440

\*"C" Models for Canadian market - Discharge port not threaded.