

PLUMBING SPECIALTIES 26-100/300/500 SERIES

Plumbing Specialties CG/CGH 26-100/26-300 Series

Compression Gauge Cocks

For draining expansion tanks, other liquid storage vessels. For condensate only.

FEATURES

- 26-100: rated up to 125 psig
- 26-300: soft metal seat/stuffing box rated up to 250 psig at 400°F
- 26-310: stainless steel ball seat/stuffing box rated up to 250 psig at 400°F



26-300

Model Number	Pipe Size (in.)	Wt./100 (lbs.)	Wheel Type
26-101	3/8	25.0	ALUMINUM
26-102	3/8	30.0	COMPOSITION
26-104	1/2	28.3	ALUMINUM
26-105	1/2	30.0	COMPOSITION
26-301	3/8	39.0	ALUMINUM
26-302	3/8	40.0	COMPOSITION
26-304	1/2	40.0	ALUMINUM
26-305	1/2	44.0	COMPOSITION
26-307	3/4	49.0	ALUMINUM
26-308	3/4	51.7	COMPOSITION
26-311	3/8	39.0	ALUMINUM
26-312	3/8	42.0	COMPOSITION
26-314	1/2	40.0	ALUMINUM
26-315	1/2	44.0	COMPOSITION
26-317	3/4	50.0	ALUMINUM
26-318	3/4	50.0	COMPOSITION
26-704	1/2	78.0	ALUMINUM
26-705	1/2	82.0	COMPOSITION
26-707	3/4	88.0	ALUMINUM
26-708	3/4	105.0	COMPOSITION

**26-100 series is not available with packing nut*

Specify the following suffix for finish: 01 - Satin Brass; 28 - Polished Brass.

Lever Operated Compression Cock 26-500 Series

For draining expansion tanks or other liquid storage vessels where the drain port is beyond reach. Spring loaded lever provides positive closure to 250 psig at 300°F.

FEATURES

- Bronze body B584 UNS C84400
- Stainless steel closure spring
- PTFE soft seat
- Graphite stem packing
- Zinc plated "S" hook on lever
- Optional 6 foot chain



Part Number	Pipe Size (in.)	Wt./100 (lbs.)	
26-504-01	1/2	110	
26-504-02	1/2	112	6' chain
26-507-01	3/4	115	
26-504-02	3/4	117	6' chain