

EZ SPAN™ REPAIR COUPLING

PVC



- Heavy PVC construction
- Double O-ring seal
- Rated at 160 PSI at 73° F
- Designed for solvent welding in new or existing pipe lines
- Complies with ASTM D1784 and D2466
- For cold water only
- Pipe must be restrained after installation

Part No.	UPC-A (032888)	Size	Inner/Master Carton Qty.	Master Weight (Lbs.)
Expands from 6-3/4" to 8-1/2"				
I60-503	605039	1/2"	1/28	9
I60-503HC	605039	1/2"	12/NA	4
Expands from 7-1/2" to 9-3/4"				
I60-504	605046	3/4"	1/24	10
I60-504HC	605046	3/4"	12/NA	6
Expands from 8-3/4" to 11-1/4"				
I60-505	605053	1"	1/15	10
I60-505HC	605053	1"	8/NA	6
Expands from 9" to 11-3/4"				
I60-506	605060	1-1/4"	1/10	10
I60-506HC	605060	1-1/4"	4/NA	4
Expands from 10" to 13"				
I60-507	605077	1-1/2"	1/16	19
I60-507HC	605077	1-1/2"	4/NA	5
Expands from 11-1/4" to 14-1/4"				
I60-508	605084	2"	1/12	20
I60-508HC	605084	2"	2/NA	3
Expands from 13" to 17-1/4"				
I60-509	605091	2-1/2"	1/3	9
Expands from 14-3/4" to 18-3/4"				
I60-510	605107	3"	1/3	12
Expands from 15" to 18-3/4"				
I60-511	605114	4"	1/3	17

POLY STREET ELBOW

PVC



- Self lubricating polyethylene construction
- Permits back and forth as well as side to side movement of riser when two elbows are used together
- Pipe threads comply with ANSI B1.20.1

Part No.	UPC-A (032888)	Size	Inner/Master Carton Qty.	Master Weight (Lbs.)
I69-403	141878	1/2"	10/500	20

TUBE & PIPE

METAL FITTINGS & NIPPLES

PLASTIC FITTINGS & NIPPLES

VALVES

FAUCETS & BATH ACCESSORIES

SPECIALTIES

