



VP14MB



VP14

VP14ENC



SBMS

Designed specifically for installations that may be targeted by vandals, the VP14 system from Atlas Sound provides highly intelligible speech reinforcement with the added benefit of extreme ruggedness. To address division of labor requirements components are ordered separately.

The VP14MB vandal resistant slanted wall mount baffle, finished in attractive, neutral beige, is ideal for use in high-security areas such as schools and correctional facilities. Its 14-gauge sturdy baffle construction and specially designed protective labyrinth screen protects the enclosed speaker assembly against abuse. Each package contains a high-quality 8" diameter loudspeaker with a 10 oz ceramic magnet and pre-assembled 25V / 70.7V transformer with five power taps terminated to a Euro block style connector. **This connector includes 3 empty blocks to allow through connection of other devices such as call switches or intercom phones without the need for wire nuts.**

The VP14ENC 16-gauge enclosure for use with model VP14MB baffle includes an adapter to comply with Wiremold™ 500 and 700 series conduit. This adapter can be installed securely through any of the knockouts that are included on all four sides of the VP14ENC. This provides a clean installation where surface mount raceways are required. All knockouts are finished completely flush before the enclosure is painted making them invisible to any would-be perpetrator.

Install the SBMS clamp-mounting loudspeaker assembly wherever paging, intercom, and background music is desired in open ceiling applications. **This ready-to-install unit combines exceptional performance and fast installation into one complete package making the SBMS ideal for use in open ceiling venues** such as: retail superstores, warehouses, light industrial facilities, multi-purpose athletic buildings, cafeterias, and convention / civic centers.

Pre-assembled unit feature an 8" dual-cone loudspeaker with a 25V / 70.7V transformer mounted within a square enclosure with matching baffle. Loudspeaker selection includes a 25 watt, 10 oz dual cone loudspeaker. Assemblies include two, easy-to-secure screw-down clamps mounted to the top of the enclosure. Clamps provide quick and easy mounting onto beams, girders, and other surfaces (max. 1/2" thick) common to open-ceiling installations. The square SBMS package includes a 734in³ (.47m²) enclosure paired with an attractive square baffle. This grille features one-piece, CRS construction. The SBMS is infinitely flexible, complying with a variety of conduit requirements. Integral knockouts facilitate 1/2" and 3/4" conduit where required by code and integral ROMEX®-style connector simplifies installation for applications where conduit is not required at all. Assemblies are shipped ready for installation with lead wires extending out of the enclosure through a wire-securing cable clamp. Finish is white powder coat epoxy.



WD417

WD Series

Attractive surface mounting loudspeaker packages with 5 oz magnet and choice of 25V or 25V / 70.7V transformer are mounted in a sloped baffle with black fabric grille. Model with (V) suffix includes volume control option.

Also available model 417-8WD enclosure only (no loudspeaker).