



EZHD72W

EZHD72W

Patented EZ Mount assembly is designed for use in standard 2' x 4' lay-in ceiling installations when backboxes are not required. EHD72W has pre-mounted brackets and installs quickly with wingnuts to the support rails provided.


Note: EZ Series will not accept an enclosure. For installations that require a backbox, see EZ Mount enclosure system on page 61.



FD25W

HD Series / FD Series

Industry-favorite loudspeaker packages for ceiling installations. Packages include loudspeaker with 5 oz (FD) or 10 oz (HD) magnet, choice of transformer and grille.



D161-8



G161-8

D Series / G Series


Quality loudspeaker packages for ceiling or wall installation include loudspeaker with 10 oz, D Series, or 5 oz, G Series, magnet and dual-voltage transformer.



L20-400-7

Designed for systems requiring secondary supervision using signal presence method. When the primary voice coil is excited the secondary voice coil induces output signal to a separate, dedicated supervisory line indicating "good" voice coil integrity back to the system.

Use caution when using L20-400-7 for dual source applications (separate amps feeding each voice coil in a paging or music application). No isolation between voice coils is provided (nor possible) so signal bleed between systems is possible.



B161-4



EZB161-4



B51-4



BT720-4-T47

B Series

The popular FC104 high-compliance 4" loudspeaker is available with transformer premounted to a selection of standard screw-mount and labor-saving torsion spring (T) grilles. For additional convenience, time and cost savings, two models are available with the patented EZ Mount installation system for applications which do not require a backbox.

Model	Transformer	Baffle
B51-4	25V/70.7V	51-4
B161-4	25V/70.7V	161-4
EZB161-4	25V/70.7V	T161-4 with Mounting Rails
BT720-4	25V/70.7V	T720-4
BT720-4-T47	70.7V	T720-4