


ANTI-SIPHON FROST FREE SILLCOCK

CHROME PLATED BRASS



- Meets NSF approved low lead standards
- CSA Certified – Canadian Standards Association
- Meets ASSE standard I019
- Chrome plated body and tube
- Lead free silver solder construction
- Built in lockshield
- 3/4" hose thread outlet
- Six lobe heavy duty handle
- Notched flange for stable installation
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Solder ends comply with ANSI B16.18
- Available in Handy Carton(HC) bin box packaging



Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
1/2" Male & 1/2" Solder				
104-511	045118	4"	1/24	34
104-513	045132	6"	1/24	37
104-515	045156	8"	1/24	39
104-517	045170	10"	1/24	41
104-519	045194	12"	1/24	44
104-521	045217	14"	1/24	39
104-511HC	045118	4"	10/NA	12
104-513HC	045132	6"	8/NA	11
104-515HC	045156	8"	10/NA	13
104-517HC	045170	10"	10/NA	14
104-519HC	045194	12"	10/NA	14
104-521HC	045217	14"	5/NA	8

3/4" Male & 1/2" Female				
104-615HC	046153	8"	6/NA	8
104-617HC	046177	10"	6/NA	9
104-619HC	046191	12"	6/NA	10


- Mueller's anti-siphon frost free sillcocks protect against back siphoning.
- A built in backflow preventer checks siphoning back into the water supply
 - The sillcock drains automatically upon water shut off, if the hose is removed or open
 - For use in residential, commercial and other buildings wherever an outdoor 3/4" hose connection is needed

FROST FREE SILLCOCK

CHROME PLATED BRASS



- Meets NSF approved low lead standards
- Chrome plated brass body and tube
- Lead free silver solder construction
- Built in lockshield
- 3/4" hose thread outlet
- Six lobe heavy duty handle
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Solder ends comply with ANSI B16.18
- Available in Handy Carton(HC) bin box packaging



Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
1/2" Male & 1/2" Solder				
104-011	040113	4"	1/24	30
104-013	040137	6"	1/24	32
104-015	040151	8"	1/24	34
104-017	040175	10"	1/24	34
104-019	040199	12"	1/24	37
104-021	040212	14"	1/24	38
104-015HC	040151	8"	12/NA	15
104-017HC	040175	10"	6/NA	8
104-019HC	040199	12"	10/NA	14

3/4" Male & 1/2" Female				
104-111	041110	4"	1/24	31
104-113	041134	6"	1/24	32
104-115	041158	8"	1/24	36
104-117	041172	10"	1/24	37
104-119	041196	12"	1/24	39
104-115HC	041158	8"	10/NA	14
104-117HC	041172	10"	10/NA	14
104-119HC	041196	12"	10/NA	15

- Mueller frost free sillcocks provide a non-freezing water supply when installed in a house, apartment or other building wall.
- The sillcock drains automatically upon water shut off, if the hose is removed or open
 - Chrome plated for appearance and corrosion protection
 - Notched flange allows stable installation on siding

TUBE & PIPE

METAL FITTINGS & NIPPLES

PLASTIC FITTINGS & NIPPLES

VALVES

FAUCETS & BATH ACCESSORIES

SPECIALTIES

