

### Water Quality Meters

Keep the costs and risks of maintaining water quality, distribution and waste under control with these easy-to-use, one-touch water quality meters. Facility Managers can take control of monitoring regulatory compliance and troubleshoot corrosion in building water/waste water systems. Use for a wide range of applications including pools, aquariums, labs, aquaculture, car washes, water testing and waste water treatment.



#### WT-10 PH/mV Pen-Type Water Quality Meter

Useful in a wide range of applications including pools, aquariums, labs, aquaculture, car washes, water testing and waste water treatment.

- Measures pH and temperature (selectable °C and °F)
- Replaceable pH electrode
- Automatic temperature compensation ensures accuracy
- Convenient pen size with pocket clip and easy-to-read, 45°-angle display
- Waterproof and dustproof, IP67-rated
- Hold, min/max, record

**INCLUDED ACCESSORIES:** Users manual, batteries, carrying case

#### WT-20 Conductivity / TDS Pen-Type Water Quality Meter

- Measures conductivity, TDS (adjustable from 0.4 to 1.0) and temperature (selectable °C and °F)
- Waterproof and dustproof, IP67-rated
- Pen size fits in a pocket
- Convenient membrane keypad

**INCLUDED ACCESSORIES:** Users manual, batteries

#### WT-30 Salinity Pen-Type Water Quality Meter

- Measures salinity (NaCL) and temperature (selectable °C and °F)
- Built-in NaCL temperature coefficient, and NaCL conductivity-to-TDS conversion factor
- Waterproof and dustproof, IP-67 rated
- Data hold
- Pen size fits in a pocket

**INCLUDED ACCESSORIES:** Users manual, batteries

FEATURE	WT-10	WT-20	WT-30
pH	0.00 → 14.00 (±0.01 pH)	–	–
Conductivity	–	0 uS → 1999 uS, 0 mS → 19.99 mS	–
TDS	–	0 → 1999 ppm / 0 → 19.99 ppt	–
Salinity	–	–	0.00 → 70.0 ppt
mV	–	–	–
Dissolved Oxygen	–	–	–



For detailed specifications go to [www.Amprobe.com](http://www.Amprobe.com)



**ORDERING INFORMATION**

- WT-10 PEN TYPE PH METER
- WT-20 CONDUCTIVITY / TDS PEN
- WT-30 SALINITY PEN

### WT-40, WT-70 and WT-80 PH/ORP Water Quality Meters

Check the pH or ORP in pools, spas, aquariums, labs, aquaculture, sanitation plants, car washes, hydroponics, water and wastewater treatment plants.

- Displays pH / mV and temperature (selectable °C and °F)
- pH electrode with automatic temperature compensation for accuracy
- USB port for data download to a PC
- Backlight display for visibility in dim areas
- Min/max and data hold

**INCLUDED ACCESSORIES:** Users manual, batteries, carrying case, probe pH standard solution (WT-40 only)

### WT-50 Dissolved Oxygen Water Quality Meter

Monitor oxygen levels for fish and shrimp farming, check the quality of industrial plant water intake and discharge, test biochemical oxygen demand for environmental water quality, or take quick, accurate dissolved oxygen readings in laboratories and schools.

- Accurate dissolved oxygen and temperature (selectable °C and °F) measurements
- Salinity and barometric pressure compensation
- Built-in memory stores up to 99 measurements with time and temperature
- USB port for downloading data to a PC
- Min/max, data hold
- Backlight for visibility in dim lighting

**INCLUDED ACCESSORIES:** Users manual, batteries, carrying case, probe pH standard solution, syringe, membrane, O-ring

### WT-60 Conductivity / TDS Water Quality Meter

- Measures conductivity, TDS, and temperature (selectable °C and °F)
- Automatic and manual temperature compensation
- Cell content normalization with selectable temperature
- Selectable conductivity to TDS conversion factor
- Backlit display for visibility in dim areas
- Auto or manual ranging, data hold
- USB download capabilities

**INCLUDED ACCESSORIES:** Users manual, batteries

FEATURE	WT-40	WT-50	WT-60	WT-70	WT-80
pH	0.00 → 14.00	–	–	–	0.00 → 14.00
Conductivity	–	–	0 → 19.99, 199.9, 1999 uS/cm/ 0 → 19.99, 0 → 199.9 mS/cm	–	–
TDS	–	–	0.00 → 19.99ppm, 0.0 → 199.9ppm, 0 → 1999ppm / 0.0 → 19.99ppt, 0 → 199.9ppt	–	–
Salinity	–	0.0 → 50.0 ppt	–	–	–
mV	-199.9 → 199.9 mV, -1999 → 1999 mV	–	–	-199.9 → 199.9 mV, -1999 → 1999 mV	-199.9 → 199.9 mV, -1999 → 1999 mV
Dissolved Oxygen	–	0.0 → 199.9 %, 0.00 → 19.99 ppm	–	–	–



For detailed specifications go to [www.Amprobe.com](http://www.Amprobe.com)



**ORDERING INFORMATION**

- WT-40 DUAL DISPLAY PH, MV & TEMP METER
- WT-50 DISSOLVED OXYGEN METER
- WT-60 CONDUCTIVITY/TDS/TEMP METER
- WT-70 ORP/ TEMPERATURE METER
- WT-80 PH/ORP METER