

Class 250 Gate Valve 620F (6GA) Series Apollo International

Non Rising Stem,
Bolted Bonnet

The Apollo Model 620F flanged cast iron gate valve provides full flow capabilities. The Apollo Gate valve can reliably be installed in most plumbing and heating systems (or building service piping).



FEATURES

- Compatible with ANSI 250# & 300# Flanges
- Full Port
- Bronze Mounted Seat Rings
- Solid Wedge
- Adjustable Graphite Stem Packing
- Non-Rising Stem
- Flanged Connection
- Bolted Bonnet
- Rugged Ductile Iron Hand Wheel
- Back Seat Protection

STANDARDS

MSS SP-70, "Gray Iron Gate Valves Flanged and Threaded"

ASME B16.10, "Face-to-Face and End-to-End Dimensions of Valves."

PERFORMANCE RATING

Saturated Steam:
250 psi (17.2 Bar) to 406°F(207°C)

Cold Working Pressure:
500 psi (34.5 Bar) at 100°F

Temperature Range:
-20°F to 406°F

Material Specifications

Part	Material
Body	Cast Iron (ASTM A126 CL-B)
Seat Rings	Cast Bronze (ASTM B62)
Wedge Face Rings	Cast Bronze (ASTM B62)
Wedge	Cast Iron (ASTM A126 CL-B)
Wedge Nut	Cast Bronze (ASTM B62)
Stem	Brass (ASTM B16)
Body Gasket	Graphite
Bolts	Carbon Steel (ASTM A307 B)
Nuts	Carbon Steel (ASTM A307 B)
Bonnet	Cast Iron (ASTM A126 CL-B)
Gland Follower Bolts	Carbon Steel (ASTM A307 B)
Stuffing Box Gaskets	Graphite
Stuffing Box	Cast Iron (ASTM A126 CL-B)
Packing	Graphite
Gland Follower	Ductile Iron (ASTM A536 65-45-12)
Packing Gland	Cast Bronze (ASTM B584)
Handwheel	Cast Iron (ASTM A126 CL-B)
Nameplate	Aluminum
Washer	Carbon Steel (ASTM A307 B)
Handwheel Nut	Ductile Iron (ASTM A536 65-45-12)

Order Information

Size	Part Number
2"	6GA-208-B1
2-1/2"	6GA-209-B1
3"	6GA-200-B1
4"	6GA-20A-B1
5"	6GA-20B-B1
6"	6GA-20C-B1
8"	6GA-20E-B1
10"	6GA-20G-B1
12"	6GA-20H-B1

Dimensions

Size	Height (open)	Length	Weight (Lbs.)
2"	11.28	8.50	42
2-1/2"	12.72	9.50	55
3"	13.31	11.00	66
4"	16.18	12.00	115
5"	19.80	15.00	161
6"	22.00	16.00	205
8"	25.59	16.50	278
10"	30.31	18.00	456
12"	33.90	19.75	633