

## DUAL WASHING MACHINE VALVE • 125 PSI

BRONZE



Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
<b>Threaded</b>				
102-207 ◊	022072	1/2"	1/24	32
102-207RP †	300125	1/2"	4/12	17
102-207HC ◊	022072	1/2"	5/NA	6
<b>Solder</b>				
102-208	022089	1/2"	1/24	29
102-208RP †	300132	1/2"	4/12	15

- Ball valve design
- Heavy brass construction
- 3/4" hose thread outlet
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Solder ends comply with ANSI B16.18
- 102-207RP is 1/2" male thread with inside 1/2" solder connection
- 102-208(RP) is 1/2" solder 90° elbow inlets
- Available in Handy Carton (HC) bin box packaging

† = Display packaging  
 ◊ = 1/2" Male external threads and 1/2" internal solder connection

## REPLACEMENT WASHING MACHINE VALVES • 125 PSI

CHROME PLATED BRASS



Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
102-209*	022096	1/2" MIP and 1/2" CxC	10/60	34
102-210**	022102	1/2" MIP and 1/2" CxC	10/60	34

\* Red Handle- for hot water  
 \*\* Blue Handle- for cold water

- For use with washing machine outlet boxes
- Easy quarter-turn ON & OFF
- Meets NSF approved low lead standards for potable water
- Chrome plated for appearance & corrosion control
- Ball valve design ensures ease of operation even after long periods of time
- Solid brass construction eliminates leaks
- Includes ABS mounting nut for easy installation into washing machine outlet box
- 3/4" hose thread outlet accepts standard washing machine hose
- Maximum 125 PSI working pressure
- 1/2" male external threads and 1/2" internal solder connection
- Hose end threads comply with ANSI B1.20.7
- Pipe threads comply with ANSI B1.20.1
- Solder end complies with ANSI B16.18

## HOSE BIBB • 125 PSI

BRASS



Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
103-013 ◊	030138	1/2"	12/72	38
103-014	030145	3/4"	12/72	40
103-013HC ◊	030138	1/2"	25/NA	13
103-014HC	030145	3/4"	12/NA	8

- Meets NSF approved low lead standards
- Heavy brass construction
- Neoprene seal washer
- 3/4" hose thread outlet
- Large flow rate
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Available in Handy Carton (HC) bin box packaging

◊ = 1/2" Male external threads and 1/2" internal solder connection

TUBE & PIPE

METAL FITTINGS & NIPPLES

PLASTIC FITTINGS & NIPPLES

VALVES

FAUCETS & BATH ACCESSORIES

SPECIALTIES

