



FAP40T



FAP40T Installed



FAP40T Installed

FAP40T

Designed for high performance in a very compact footprint, the FAP40T appeals to system designers and architects, and is ideal for high-intelligibility voice, music, and signal reproduction in commercial, industrial, and institutional applications. A unique tap selector switch allows for easy system tuning with a full selection of taps up to 16 Watts (with 8Ω bypass). This switch also functions as a diffuser cone, providing smooth, even dispersion of the high frequency content from the center of the 4" polypropylene driver. The high frequency response is so natural that many assume the driver is a coaxial design instead of a single

cone driver. Low frequency response is enhanced by the tuned and ported enclosure. The FAP40T is UL1480 listed and the enclosure is constructed of high impact injection molded plastic and includes a press fit grille design that blends well with contemporary architecture.

A 2-pole terminal block with a removable metal cover allows for easy system wiring as well as "daisy chain" wiring to other FAP40Ts or even FAPSUB subwoofers (a great combination).

A Tile Bridge is included in the package for suspended ceiling applications. The light weight

design of the FAP40T coupled with the "Dog Leg" mounting system makes additional drywall support unnecessary in most installations.

For new construction drywall ceiling applications, the optional FA-TR4 trim ring is available to provide a marked location for drywall installers to cut around, essentially reserving the FAP40T's desired location until final installation. Mounting holes are provided to accommodate 16" or 24" OC stud / joist mounting. The FAP40T also includes a secondary support point built into the termination cover. This "ring" may be used with an auxiliary support cable in drop tile installations.