

WAFER CHECK VALVES 6WC SERIES

Class 125 Wafer Check 910WE (6WC) Series Apollo International

Flanged Connection

The Apollo Model 910WE Cast Iron Wafer Check valve provides full flow capabilities. It provides reliable and economical protection against reverse flow. The Apollo Wafer Check valve can reliably be installed in most plumbing and heating systems (or building service piping).



FEATURES

- Compatible with ANSI 125# & 150# Flanges
- Full Port
- Minimal Pressure Drop
- Flanged Connection
- Light Weight
- Spring Assisted Closing for Quicker Response

PERFORMANCE RATING

Saturated Steam:
125 psi (8.6 Bar) to 353°F(178°C)

Cold Working Pressure:
200 psi (13.8 Bar) at 100°F

Temperature Range:
-20°F to 406°F

Material Specifications

Part	Material
Body	Cast Iron (ASTM A126 CL-B)
Seat Ring	EPDM
Disc	Aluminum Bronze
Spring	Stainless Steel 316
Stem	Stainless Steel 316
Screw	Carbon Steel
Pin	Stainless Steel 316

Order Information

Size	Part Number
2"	6WC-108-E1
2-1/2"	6WC-109-E1
3"	6WC-100-E1
4"	6WC-10A-E1
5"	6WC-10B-E1
6"	6WC-10C-E1
8"	6WC-10E-E1
10"	6WC-10G-E1
12"	6WC-10H-E1

Dimensions

Size	Diameter	Length	Weight (Lbs.)
2"	4.00	2.12	5
2-1/2"	4.75	2.38	7
3"	5.25	2.62	10
4"	6.75	2.62	16
5"	7.50	3.25	25
6"	8.50	3.75	30
8"	11.00	5.00	78
10"	13.25	5.50	113
12"	16.00	7.12	157