


# SAFETY AND RELIEF VALVES DRIP PAN ELBOW

## Accessories Drip Pan Elbow

The use of a drip pan elbow is highly recommended for steam service safety valves. When attached to a safety valve outlet, these elbows collect and remove condensate as well as isolate the valve from discharge piping stresses. Elbows through 4" feature female NPT threads and connect to the valve outlet by means of a close nipple. The 6" and 8" elbows have integral 125# ANSI B16.1 flanges and bolt directly to the valve outlet.



Part Number	Inlet in (mm)	A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	G NPT	Weight lbs.(kg)
DPE07	3/4 (20)	2.00 (51)	3.75 (95)	1.88 (48)	2.00 (51)	1.00 (25)	1.50 (38)	1/4	2 (1)
DPE10	1 (25)	2.00 (51)	3.75 (95)	1.88 (48)	2.00 (51)	1.00 (25)	1.50 (38)	1/4	2 (1)
DPE12	1-1/4 (32)	2.00 (51)	5.50 (140)	2.47 (63)	4.13 (105)	1.44 (37)	2.13 (54)	3/8	7.5 (3)
DPE15	1-1/2 (40)	2.00 (51)	5.50 (140)	2.47 (63)	4.13 (105)	1.44 (37)	2.13 (54)	3/8	7.5 (3)
DPE20	2 (50)	3.00 (76)	6.25 (159)	2.31 (59)	3.63 (92)	1.63 (41)	2.25 (57)	1/2	8.5 (4)
DPE25	2-1/2 (65)	4.00 (102)	7.38 (187)	3.00 (76)	4.31 (109)	1.94 (49)	2.69 (68)	3/4	12 (5)
DPE30	3 (80)	4.00 (102)	8.00 (203)	3.50 (89)	4.88 (124)	2.31 (59)	3.13 (80)	3/4	19 (9)
DPE40	4 (100)	6.00 (152)	9.63 (245)	4.50 (114)	5.75 (146)	2.88 (73)	3.75 (95)	3/4	25 (11)
DPE60	6 (150)	8.00 (203)	12.75 (324)	6.63 (168)	7.44 (189)	4.19 (106)	8.00 (203)	3/4	105 (48)
DPE80	8 (200)	10.00 (254)	16.50 (419)	7.50 (191)	9.44 (240)	5.38 (137)	10.75 (273)	1	202 (92)

Note: Ordering size of drip pan elbow is also nominal outlet size of safety valve.