Complex Problems

Today's outdoor sports facilities demand sound systems capable of delivering exceptional sound quality, high output and precise pattern control.

Coverage patterns and mounting scenarios vary greatly – One size will *not* fit all!

Installation hardware has to be included or made easy with the implementation of 3rd party mounting solutions.

Atlas Solutions

AH Series Stadium Horn Systems from Atlas Sound


- Precision engineered dispersion patterns provide maximum SPL capabilities while maintaining audio integrity and intelligibility.
- 8", 12", & 15" solutions, each available in three popular coverage patterns: 50° x 40°, 65° x 65°, & 90° x 40° for 15" models, 90° x 90°, 65° x 65°, & 90° x 40° for 8" & 12" models.
- All models (except AHSUB15S) include a versatile stainless steel mounting bracket. Alternatively, Atlas Sound offers Allen Products mounting solutions for easy pole mount installation.





Ask your Atlas Representative for details and discover how the simple solution is the Atlas Solution!

Learn more about how Atlas can solve your complex problems @ AtlasSound.com or call 800-876-3333





ISO9001-2000





Atlas Sound

The AH Series Stadium Loudspeakers offer the most often requested coverage patterns while providing excellent intelligibility for the most challenging environments including large auditoriums & sport fields. With a complete family of 8", 12", and 15" 2-way systems, designers and specifiers can select models for whatever SPL is required with the peace of mind that all units will provide outstanding pattern control.

90° H X 90° V models (8" and 12" models only) are suggested for shorter loudspeaker to listener distances and/or wider coverage requirements such as bleacher seating where the speaker may be in close proximity to the crowd.

 65° H X 65° V (8", 12" and 15" models) square coverage pattern models are perfect for down-firing applications including convention centers.

90° H X 40° V patterns (8", 12" and 15" models) work well when longer speaker to listener distances require a tighter vertical coverage pattern.

15" AH series models offer an even slightly tighter pattern of 50° H X 40° V. This device is often mounted atop football field press boxes with the device aimed at the visitor side in conjunction with wider coverage pattern models to cover the home side bleachers.



Common Design Features

Multiple stainless steel mesh screens protect internal drivers from weather and pest damage. A primary rodent screen provides protection for all components, a secondary screen resides between the high frequency horn and the driver, and a third perforated screen protects the woofer.

Heavy-duty stainless steel mounting brackets are included with all models and three drop-forged eyebolts are also included for overhead suspension (use only load-rated & approved hardware). For light pole mounting Atlas Sound also distributes matching mounting accessories from Allen Products. (see back)

15" models AH9040S, AH6565S and AH5040S feature impressive, full range sound reproduction via a high excursion low frequency woofer and a concentrically mounted 1" exit compression driver.

A well-designed, highly efficient internal passive crossover network ensures proper transition between the two drivers, which collectively provide frequency response from 75 Hz – 14.5 kHz (±5dB).

With an efficiency rating in excess of 102dB (1W / 1M), the 15" AH Series is a perfect choice for high-energy music playback at sporting events and extended range speech reinforcement for large venue emergency notification. The 8Ω rating allows maximum low frequency response and is a good match with Atlas Sound model CP700 amplifier. If transformer operation is required for long runs of smaller gauge cable please contact tech support for proper configuration and use of model AF140 auto-former. Termination is via rear mounted terminal block with a Plexiglas cover for weather resistance.

The 8" & 12" 2-way models are perfect for applications where space considerations will not allow installation of the larger 15" 2-way models. All 8" & 12" models include a 60 watt, 70.7V / 100V internal transformer which is accessed via terminal block connector sealed by a weather resistant cover. Transformer may also be bypassed for direct coupled 8 Ω operation.

12" AH models feature a version of the popular 12CXT60 compression driver coaxial loudspeaker.

8" 2-way AH models feature a version of the popular 8CXT60 compression driver coaxial loudspeaker.







15" Stadium Subwoofer

A perfect complement to any AH Series full range device, the AHSUB15S will provide extended low frequency response to add presence to any high energy music playback system. A specially designed, rear firing 15" cast frame woofer is mounted into a high volume chamber for optimum loading and output. These design elements provide an impressive frequency response down to 55 Hz (-5dB) for accurate bass response. The AHSUB15S is capable of handling up to 250 watts RMS, providing output in excess of 126dB (Rated power @ 1 Meter). Three eyebolt suspension points are provided along with mounting locations to allow stacked installation of other AH models.

Subwoofer Mounting Solutions

AHSUBSTAND allows the easy installation of the AHSUB15S under bleacher seating or other areas where concrete slab mounting is possible. Stand provides secure mounting of the AHSUB15S in a down firing configuration to maximize output performance while helping to prevent theft and weather damage.

Holes are provided on the bracket feet for anchor points when mounting on concrete slab and additional holes are located on the frame to allow the AHSUB15S to be attached to the frame via chain or cable (not included) for optimal security.



AHSUBSTAND



Allen Products - Mounting Solutions

As a convenience to our dealers Atlas Sound is proud to provide quality mounting solutions from Allen Products to facilitate pole mounting of the AH Series Stadium Horns. Please call Atlas Sound Customer Service at 800.876.3333 for assistance in choosing the correct hardware for your installation. Application drawings are available at www.atlassound.com. Safety cables are strongly recommended on all installations.

Note: Installation of this product must only be implemented by a qualified contractor.


Before purchasing the necessary parts we recommend you review all documentation and have a complete understanding of the requirements for your installation. Every installation is different and there are many options available to meet the installation requirements. Some slight modifications may be required to the product to meet the installation requirements.

AH Series Application Guides

- Single AH Pole Mount 8", 12", & 15"
- Double AH Pole Mount 8", 12", & 15"
- Tipple AH Pole Mount 8", 12", & 15"
- Safety Strap Install Guide
- AH/Pole Star Install Guide







gle Pole Mount Double Pole Mount Application Application

Available Parts (Call for Availability)

Pole Mount Components

AH-PM-BAND-20S
AH-PM-BAND-30
AH-PM-BAND-30
AH-PM-BAND-60
AH-PM-BAND-60
AH-PM-BAND-90
AU-PM-BAND-90
AU-PM-BAND-9

AH-PM-DA-24
 AH-PM-DA-36
 AH-PM-DA-48
 Dual Adaptor, 36" extension
 Dual Adaptor, 48" extension

• AH-PM-MOUNT-6DOWN Pole Adaptor Bracket 2" - 6" pole diameter 150 lbs max., Support Bands sold separately

AH-PM-MOUNT-6UP
 AH-PM-SA-12
 Pole Adaptor Bracket 6" or greater pole diameter 300 lbs max., Support Bands sold separately
 Support Arm, 12" extension

AH-PM-SA-18 Support Arm, 18" extension
 AH-PM-SA-24 Support Arm, 24" extension
 Support Arm, 24" extension


Safety Anchor & Cables

AH-SK-025-S

AH-PM-SAFETY-6DOWN
 Safety Anchor, for pole diameters 2" and up, Support Bands sold separately

AH-CC-096-S
AH-FC-030-S
AH-FC-033-S
AH-FC-033-S
AH-FC-043-S
AH-FC-043-S
AH-FC-043-S
AH-TB-025
Safety Cables Qty. 2, adjustable to 90" silver, galvanized
Pole Mnt Sfty Cable 30" Pr, X2 Shackles, X2 Tie Wrap
Pole Mnt Sfty Cable 43" Pr, X2 Shackles, X2 Tie Wrap
Pole Mnt Safety Cable Eye To Eye Turnbuckle

Shackle Assembly



Safety Strap Single Pole Mount Application

Model	Power Handling	Impedance / Transformer Taps	Sensitivity (1W / 1M)	Frequency Response	Dispersion (H x V)	Height	Width	Depth
AH5040S	250 Watts	8Ω	104dB	75Hz –14.5kHz	50° x 40°	23.75" (603.25mm)	21.41" (543.81mm)	30.07" (763.78mm)
AH6565S	250 Watts	8Ω	102dB	75Hz –14.5kHz	65° x 65°	23.75" (603.25mm)	21.41" (543.81mm)	30.08" (764.03mm)
AH9040S	250 Watts	8Ω	102dB	75Hz –14.5kHz	90° x 40°	24.91" (632.71mm)	29.57" (751.08mm)	29.65" (753.11mm)
AH99-12ST	200 Watts	7.5 ,15, 30, & 60 Watts / 8Ω	103dB	80Hz –14kHz	90° x 90°	25.68" (652.27mm)	22.06" (560.32mm)	22.57" (573.28mm)
AH94-12ST	200 Watts	7.5 ,15, 30, & 60 Watts / 8Ω	103dB	80Hz –14kHz	90° x 40°	24.68" (626.87mm)	22.06" (560.32mm)	22.57" (573.28mm)
AH66-12ST	200 Watts	7.5 ,15, 30, & 60 Watts / 8Ω	102dB	80Hz –14kHz	65° x 65°	23.88" (606.55mm)	21.41" (543.81mm)	22.57" (573.28mm)
AH99-8ST	100 Watts	7.5 ,15, 30, & 60 Watts / 8Ω	101dB	90Hz – 10kHz	90° x 90°	21.88" (555.75mm)	19.66" (499.36mm)	19.73" (501.14mm)
AH94-8ST	100 Watts	7.5 ,15, 30, & 60 Watts / 8Ω	101dB	90Hz – 14kHz	90° x 40°	20.05" (509.27mm)	19.66" (499.36mm)	19.73" (501.14mm)
AH66-8ST	100 Watts	7.5 ,15, 30, & 60 Watts / 8Ω	100dB	90Hz – 14kHz	65° x 65°	20.95" (532.13mm)	17.91" (454.91mm)	20.98" (532.89mm)
AHSUB15S	250 Watts	8Ω	103dB	55Hz – 120Hz	OMNI	30.56" (776.22mm)	30" (762mm)	28.16" (715.26mm)

Learn more about how Atlas can solve your complex problems

@ AtlasSound.com or call 800-876-3333



ISO9001-2000



