


SAFETY AND RELIEF VALVES 16-500, 17 SERIES

Calibrated Pressure Relief Valves

Allows for in-line pressure adjustments without the need for a pressure gauge. Provides static overpressure protection for liquid filled systems such as well pumps, tanks, and fire protection systems.

FEATURES

- 1/2" or 3/4" inlet connection
- Factory preset at 100 psi
- Pressure range 50 to 175 psi, calibrated in 25 psi increments
- Cast bronze body, SS springs
- Silicone soft seat, EPDM cap seal
- Maximum service temp: 200°F



Part Number	Size (in.)	Wt./100 (lbs.)	Dimensions (in.)		
			A	B	C
16-503-01	1/2 M x 1/2 F	37	1.31	3.44	1.00
16-504-01	3/4 M x 1/2 F	37	1.31	3.44	1.00

Hot Water Relief Valves RVW17 (17-400) Series

Pressure Relief Valves

Prevents excessive thermal expansion buildup in plumbing systems, tank applications and tankless water heaters. Conforms to HUD/FHA requirements: ideal for well systems.

FEATURES

- Bronze body, stainless steel spring
- CSA certified design to ANSI Z21.22 "Relief Valves for Hot Water Supply Systems"
- ASME capacity certified from 75 to 150 psig*
- CRN #0G8547.5C Registered in all Canadian Provinces and Territories



Model Number	Size (in.)	CSA Capacity		*ASME Certified Discharge Capacities BTU/HR.			
		Rating (BTU/Hr)	Wt./100 (lbs.)	75	100	125	150
17-401	1/2 M x 1/2 F	15,000	57	-	-	-	-
17-402	3/4 M x 3/4 F	200,000	53	505,000	648,000	791,000	934,000

Note: When ordering specify pressure by adding the two digit key number after the product number as follows: 75 psig - 01; 100 psig - 02; 125 psig - 03; 150 psig - 04; 160 psig - 05
 * 3/4 model only: National Board Capacity Certified - BTU per hour (90% of actual capacity at 10% accumulation) ASME boiler and pressure vessel code - Section IV - Heating Boilers