



FAP42TC

FAP42TC

With an overall depth of 4" (108mm), the FAP42TC is the perfect choice for high fidelity audio and wide, even coverage when space above the plenum is limited. For wall mount applications (tanning salons or surround sound), the shallow depth fits in most studded walls. The popular C-Ring/V-Rail mounting system provides quick installation into drop tile acoustic ceilings and existing drywall. The optional FAP42-TR may be used for new construction drywall applications.

The FAP42TC includes all the popular FAP42T features: front mounted tap selector switch (with 8Ω bypass), press-fit grilles, high performance 4" poly cone driver with PEI tweeter, and precision crossover components for smooth, even coverage.

FAP42TC-UL2043

The New FAP-UL2043 Series models from Atlas Sound meet requirements of UL 2043 for loudspeakers used in air handling (true plenum) spaces.

FAP42-RR

The FAP42-RR "Retro Ring" allows the FAP42T or FAP42TC to be installed into a typical 8" loudspeaker cutout up to 12". Kit consists of a 13¾" oversized trim ring and four extension "Dog Legs". The C-Ring/V-Rail included with the FAP42T/FAP42TC mounts atop the tile as normal through the center hole of the FAP42-RR. The extended dog legs are tightened and the entire assembly is flush to the ceiling.



FAP42RR



FA42T-6MB

FA62T-8MB

FA42T-6MB / FA62T-8MB

Atlas Sound addresses retrofit and "division of labor" installations with "motor board" versions of the Strategy Series® II.

Model FA42T-6MB and FA62T-8MB are the entire speaker / transformer / selector switch / front plate assembly found in the FAP42T and FAP62T. The footprints are identical to a standard FA series 6" or 8" speaker component and allow the motor board to fit into current Strategy Series® enclosures of those sizes. The FAP42T fits in the same manner as a regular 6" FA Series speaker and the FAP62T fits in the same manner as an 8" FA Series speaker.