

# PE X COPPER FITTINGS



## CON-STAB ID SEAL® PE Stab x Copper Transition Couplings

PE SIZE	WALL	COPPER TUBE SIZE	PART NUMBER (3408/4710)
1/2" CTS (5/8" OD)	.090	1/4" OD	9943-99-0062-00
		3/8" OD	9943-99-0063-00
		1/2" OD	9943-99-0064-00
		5/8" OD	9943-99-0065-00
3/4" IPS	SDR-11 (.095)	5/8" OD	9943-99-0066-00



- For sizes not listed, contact Continental Industries.
- Con-Stab ID Seal® fittings rated at 125 psig.
- Recommended accessories;
  - Continental's Bladed Chamfering Tool. See page 30 for size combinations available.
- 45° Copper Flare made in accordance with SAE J513.
- Forged Flare nut made to ASTM B 283.

## PA COMPRESSION FITTINGS PE Compression x Copper Adapter Couplings

PE SIZE	WALL	COPPER TUBE SIZE	PART NUMBER
1/2" CTS (5/8" OD)	.090	3/8" OD	9957-48-0057-00
	.062		9957-48-0058-00
1/2" CTS (5/8" OD)	.090	5/8" OD	9957-48-0054-00
	.062		9957-48-0059-00



- For sizes not listed, contact Continental Industries.
- PA Compression fittings rated at 125 psig.

## PVC COMPRESSION FITTINGS PE Compression x Copper Adapter Couplings

PE SIZE	WALL	COPPER TUBE SIZE	PART NUMBER
1/2" CTS (5/8" OD)	.090	1/2" OD	9957-48-0031-00
	.062		9957-48-0060-00
1" CTS (1 1/8" OD)	.099/.101	7/8" OD	9957-48-0061-00
	.090		9957-54-0091-00
1" CTS (1 1/8" OD)	.099/.101	1 1/8" OD	9957-99-0062-00
	.090		9957-99-0081-00



- For sizes not listed, contact Continental Industries.
- PA Compression fittings rated at 125 psig.

## STEEL COMPRESSION FITTINGS PE Compression x Copper Adapter Couplings

PE SIZE	WALL	COPPER TUBE SIZE	PART NUMBER
1/2" CTS (5/8" OD)	.090	1/2" OD	0343-00-1004-00
		5/8" OD	0443-00-1004-00
3/4" CTS (7/8" OD)	.090	5/8" OD	0443-00-1006-00
1" CTS (1 1/8" OD)	.099/.101	5/8" OD	0443-00-1008-00
1/2" IPS	SDR-9.3 (.090)	1/2" OD	0343-00-1012-00
		5/8" OD	0443-00-1012-00
3/4" IPS	SDR-11 (.095)	1/2" OD	0343-00-1013-00
		5/8" OD	0443-00-1013-00
1" IPS	SDR-11 (.119)	5/8" OD	0442-00-1014-00
1 1/4" IPS	SDR-10 (.166)	5/8" OD	0443-00-1015-00



- For sizes not listed, contact Continental Industries.
- Conductive Compression Outlets rated at 300 psig.