

PE X PE FITTINGS



CON-STAB ID SEAL® PE Stab Full Couplings with Dresser® & UMAC® Excess Flow Valves

UMAC® EXCESS FLOW VALVES				
EFV SIZE	PE SIZE	WALL	PART NUMBER (3408/4710)	PART NUMBER (2406)
UMAC® SERIES 300	1/2" CTS (5/8" OD)	.090	3259-52-1004-70	3369-52-1004-70
	3/4" CTS (7/8" OD)	.090	3259-52-1006-70	3369-52-1006-70
	1" CTS (1 1/8" OD)	.099/.101	3259-52-1008-70	3369-52-1008-70
		.090	3259-52-1008-71	3369-52-1008-71
	1 1/4" CTS (1 3/8" OD)	.121	3259-52-1039-70	3369-52-1039-70
		.090	3259-52-1039-71	3369-52-1039-71
	1/2" IPS	SDR-9.33 (.090)	3259-52-1012-70	3369-52-1012-70
3/4" IPS	SDR-11 (.095)	3259-52-1013-70	3369-52-1013-70	
1" IPS	SDR-11 (.119)	3259-52-1014-70	3369-52-1014-70	
UMAC® SERIES 700	1/2" CTS (5/8" OD)	.090	3259-52-1004-72	3369-52-1004-72
	3/4" CTS (7/8" OD)	.090	3259-52-1006-72	3369-52-1006-72
	1" CTS (1 1/8" OD)	.099/.101	3259-52-1008-72	3369-52-1008-72
		.090	3259-52-1008-73	3369-52-1008-73
	1 1/4" CTS (1 3/8" OD)	.121	3259-52-1039-72	3369-52-1039-72
		.090	3259-52-1039-73	3369-52-1039-73
	1/2" IPS	SDR-9.33 (.090)	3259-52-1012-72	3369-52-1012-72
3/4" IPS	SDR-11 (.095)	3259-52-1013-72	3369-52-1013-72	
1" IPS	SDR-11 (.119)	3259-52-1014-72	3369-52-1014-72	
UMAC® SERIES 1800	1" CTS (1 1/8" OD)	.099/.101	3259-52-1008-74	3369-52-1008-74
		.090	3259-52-1008-75	3369-52-1008-75
	1 1/4" CTS (1 3/8" OD)	.121	3259-52-1039-74	3369-52-1039-74
		.090	3259-52-1039-75	3369-52-1039-75
	1/2" IPS	SDR-9.33 (.090)	3259-52-1012-74	3369-52-1012-74
3/4" IPS	SDR-11 (.095)	3259-52-1013-74	3369-52-1013-74	
1" IPS	SDR-11 (.119)	3259-52-1014-74	3369-52-1014-74	
DRESSER® EXCESS FLOW VALVES				
EFV SIZE	PE SIZE	WALL	PART NUMBER (3408/4710)	PART NUMBER (2406)
DRESSER® LOW CAPACITY	1/2" CTS (5/8" OD)	.090	3259-52-1004-76	3369-52-1004-76
	3/4" CTS (7/8" OD)	.090	3259-52-1006-76	3369-52-1006-76
	1" CTS (1 1/8" OD)	.099/.101	3259-52-1008-76	3369-52-1008-76
		.090	3259-52-1008-77	3369-52-1008-77
	1 1/4" CTS (1 3/8" OD)	.121	3259-52-1039-76	3369-52-1039-76
		.090	3259-52-1039-77	3369-52-1039-77
	1/2" IPS	SDR-9.33 (.090)	3259-52-1012-76	3369-52-1012-76
3/4" IPS	SDR-11 (.095)	3259-52-1013-76	3369-52-1013-76	
1" IPS	SDR-11 (.119)	3259-52-1014-76	3369-52-1014-76	
DRESSER® MEDIUM CAPACITY	1/2" CTS (5/8" OD)	.090	3259-52-1004-78	3369-52-1004-78
	3/4" CTS (7/8" OD)	.090	3259-52-1006-78	3369-52-1006-78
	1" CTS (1 1/8" OD)	.099/.101	3259-52-1008-78	3369-52-1008-78
		.090	3259-52-1008-79	3369-52-1008-79
	1 1/4" CTS (1 3/8" OD)	.121	3259-52-1039-78	3369-52-1039-78
		.090	3259-52-1039-79	3369-52-1039-79
	1/2" IPS	SDR-9.33 (.090)	3259-52-1012-78	3369-52-1012-78
3/4" IPS	SDR-11 (.095)	3259-52-1013-78	3369-52-1013-78	
1" IPS	SDR-11 (.119)	3259-52-1014-78	3369-52-1014-78	
DRESSER® HIGH CAPACITY	1" CTS (1 1/8" OD)	.099/.101	3259-52-1008-80	3369-52-1008-80
		.090	3259-52-1008-81	3369-52-1008-81
	1 1/4" CTS (1 3/8" OD)	.121	3259-52-1039-80	3369-52-1039-80
		.090	3259-52-1039-81	3369-52-1039-81
	1/2" IPS	SDR-9.33 (.090)	3259-52-1012-80	3369-52-1012-80
3/4" IPS	SDR-11 (.095)	3259-52-1013-80	3369-52-1013-80	
1" IPS	SDR-11 (.119)	3259-52-1014-80	3369-52-1014-80	



- For sizes not listed, contact Continental Industries.
- Con-Stab ID Seal® fittings rated at 125 psig.
- Recommended accessories:
 - Continental's Bladed Chamfering Tool. See page 30 for size combinations available.