

ACCESSORIES



PROTECTIVE SLEEVES



| CATALOG NUMBER | DIAMETER | | LENGTH | FOR USE WITH CONTINENTAL PRODUCTS | | | |
|----------------|-------------|---------|--------|---|---|--|--|
| | INTERNAL | OUTSIDE | | STEEL FITTINGS | PVC FITTINGS | PA FITTINGS | STAB FITTINGS |
| 44-2585-00 | 1.370/1.395 | 1.612 | 12" | | 1/4" OD & 7/8" OD P.E. Compression O/L's | | |
| 44-2586-00 | 1.875/1.915 | 2.190 | 12" | | 3/8" OD & 5/8" OD P.E. Compression O/L's | 3/8" OD & 5/8" OD P.E. Compression O/L's | |
| 44-2587-00 | 2.375/2.425 | 2.760 | 12" | 3/8" OD, 5/8" OD P.E. Compression O/L's | 1 1/8" OD, 1/2" IPS & 3/4" IPS P.E. Compression O/L's | 1 1/8" OD P.E. Compression O/L's | |
| 44-2588-00 | 2.375/2.425 | 2.760 | 21" | 5/8" OD, 1/2" IPS & 3/4" IPS P.E. Transition O/L's | | | |
| 44-2589-00 | 2.875 | 3.270 | 24" | 7/8" OD, 1/2" IPS P.E. Compression O/L's | 1" IPS P.E. Compression O/L's | 3/4" IPS & 1" IPS P.E. Compression O/L's | 5/8" OD, 7/8" OD, 1 1/8" OD, 1/2" IPS, 3/4" IPS & 1" IPS O/L's |
| | | | | 1 1/8" OD, 1" IPS P.E. Transition O/L's | | | |
| 44-5753-00 | 4.250 MIN. | 4.760 | 24" | 1 1/8" OD, 3/4" IPS, 1" IPS, 1 1/4" IPS & 1 1/2" IPS P.E. Compression O/L's | 1 1/4" IPS P.E. Compression O/L's | 1 1/4" IPS P.E. Compression O/L's | 1 1/4" IPS & 1 1/2" IPS O/L's |
| | | | | 1 1/4" IPS P.E. Transition O/L's | | | |
| 44-5754-00 | 5.200 MIN. | 5.820 | 36" | | 2" IPS P.E. Compression O/L's | 2" IPS P.E. Compression O/L's | 2" IPS O/L's |

NOTE: It is advisable to limit shear at main connections. In this regard, your company's policies should be followed. For further information, reference; ASTM D 2774 Standard Practice for Underground Installation of Thermoplastic Pressure Piping; Code of Federal Regulations, Title 49, Transportation Part 192; AGA Plastic Pipe Manual and/or The Guidance Manual for Operators of Small Gas Systems by the U.S. Department of Transportation.

