



FITTINGS W/ UMAC® EFV'S

CON-STAB ID SEAL® Adapter Couplings with UMAC® Excess Flow Valves (PE Stab x PE Pigtail)



UMAC® EXCESS FLOW VALVES				
EFV SIZE	PE SIZE	WALL	PART NUMBER (3408/4710)	PART NUMBER (2406)
UMAC® SERIES 300	1/2" CTS (5/8" OD)	.090	0459-48-3104-70	0469-48-3104-70
	1" CTS (1 1/8" OD)	.099/.101	0859-48-3108-70	0869-48-3108-70
	3/4" IPS	SDR-11 (.095)	1359-48-3113-70	1369-48-3113-70
	1" IPS	SDR-11 (.119)	1459-48-3114-70	1469-48-3114-70
UMAC® SERIES 700	1/2" CTS (5/8" OD)	.090	0459-48-3104-72	0469-48-3104-72
	1" CTS (1 1/8" OD)	.099/.101	0859-48-3108-72	0869-48-3108-72
	3/4" IPS	SDR-11 (.095)	1359-48-3113-72	1369-48-3113-72
	1" IPS	SDR-11 (.119)	1459-48-3114-72	1469-48-3114-72
UMAC® SERIES 1800	1" CTS (1 1/8" OD)	.099/.101	0859-48-3108-74	0869-48-3108-74
	3/4" IPS	SDR-11 (.095)	1359-48-3113-74	1369-48-3113-74
	1" IPS	SDR-11 (.119)	1459-48-3114-74	1469-48-3114-74

- For sizes not listed, contact Continental Industries.
- Con-Stab ID Seal® fittings rated at 125 psig.
- Recommended accessories;
 - Continental's Bladed Chamfering Tool. See page 28 for size combinations available.

