

## ABS metric



### Lugstyle butterfly valve type 142 ABS 24V Without manual override

**Model:**

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Voltage 24 V AC/DC
- Control time 15 s/90°<) EA31
- Control time 25s/90°<) EA42
- Control range 90°<)
- Actuator with integrated emergency manual override standard

Inch	DN [mm]	d [mm]	PN	EPDM Code
2	50	63	10	<b>199 142 542</b>
2 ½	65	75	10	<b>199 142 543</b>
3	80	90	10	<b>199 142 544</b>
4	100	110	10	<b>199 142 545</b>
5	125	140	10	<b>199 142 546</b>
6	150	160	10	<b>199 142 547</b>
8	200	225	10	<b>199 142 548</b>



### Lugstyle butterfly valve type 142 ABS 24V With manual override

**Model:**

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Voltage 24 V AC/DC
- Control time 15 s/90°<) EA31
- Control time 25s/90°<) EA42
- Control range 90°<)
- Actuator with integrated emergency manual override standard

Inch	DN [mm]	d [mm]	PN	EPDM Code
2	50	63	10	<b>199 142 522</b>
2 ½	65	75	10	<b>199 142 523</b>
3	80	90	10	<b>199 142 524</b>
4	100	110	10	<b>199 142 525</b>
5	125	140	10	<b>199 142 526</b>
6	150	160	10	<b>199 142 527</b>
8	200	225	10	<b>199 142 528</b>