


51 336 001

## Branch fitting topload



- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- Branch Fitting for assembling as Topload with tool 799.350.477; angle adaptors (799.350.340) for fusion cable required
- Electrofusion outlet with integrated pipe fixation
- Protected wire without medium contact
- 4 mm pin connectors
- Limited path fusion indicators

d [mm]	d1 [mm]	Code	GP	kg	H [mm]	L [mm]	L1 [mm]	B [mm]	d2 [mm]
280	90	<b>193 135 289</b>	5	1.180	102	260	82	243	65
280	110	<b>193 135 290</b>	5	1.280	108	260	88	243	86
280	125	<b>193 135 291</b>	5	1.480	129	260	99	243	86
315 - 355	90	<b>193 135 309</b>	5	1.180	102	260	82	249	65
315 - 355	110	<b>193 135 310</b>	4	1.280	108	260	88	249	86
315 - 355	125	<b>193 135 311</b>	5	1.480	129	260	99	249	86
400 - 450	90	<b>193 135 329</b>	5	1.180	102	260	82	256	65
400 - 450	110	<b>193 135 330</b>	4	1.280	108	260	88	256	86
400 - 450	125	<b>193 135 331</b>	4	1.280	129	260	99	256	86
500 - 630	90	<b>193 135 159</b>	5	1.060	102	260	82	263	65
500 - 630	110	<b>193 135 160</b>	5	1.160	108	260	88	263	86
500 - 630	125	<b>193 135 161</b>	4	1.360	129	260	99	263	86

PF 2 51 336 001