

# Accessories for actuated valves

## Pilot valve type 5470

- to pneumatic actuators DA (Double acting)
- Version with NAMUR connection
- Circuit function: 4/2-way valve, in rest position pressure inlet 1 connected to outlet 2, outlet 4 exhausted
- Valve material: polyamid
- Electrical connection: cable plug

## Pilot valve 4/2-ways

- For AC 50-60 Hz and DC



Voltage	DN [mm]	NBR Code
230 V, AC/DC	4	<b>199 190 302</b>
115 V, AC/DC	4	<b>199 190 303</b>
24 V, AC/DC	4	<b>199 190 304</b>

## Pilot valve type MNL532

### Model:

- With NAMUR connection and two silencers/throttle screws

### Mode of action:

- 3/2-way valve, in rest position pressure inlet 1 closed, outlet 3 exhausted
- 5/2-way valve, in rest position pressure inlet 1 connected to outlet 4, outlet 3 exhausted
- Material of body: Aluminum
- to pneumatic actuators
- Electrical connection: cable plug

## Pilot valve 3/2-5/2-ways



Voltage	DN [mm]	Inch	NBR Code
230 V, AC	5	1/8	<b>199 190 360</b>
110 V, AC	5	1/8	<b>199 190 359</b>
48 V, AC	5	1/8	<b>199 190 361</b>
24 V, AC	5	1/8	<b>199 190 358</b>
24 V, DC	5	1/8	<b>199 190 357</b>