

PROGEF Standard metric



PROGEF Standard Lugstyle butterfly valve type 568 Bare shaft

Model:

- Material: PP-H
- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Interface F07 according to DIN/ISO 5211

Inch	DN [mm]	PN	EPDM Code	FPM Code	
2	50	10	167 568 902	167 568 922	
2 ½	65	10	167 568 903	167 568 923	
3	80	10	167 568 904	167 568 924	
4	100	10	167 568 905	167 568 925	
5	125	10	167 568 906	167 568 926	
6	150	10	167 568 907	167 568 927	
8	200	10	167 568 908	167 568 928	



PROGEF Standard Lugstyle butterfly valve type 242 FC (Fail safe to close) Without manual override

Model:

- Material: PP-H
- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Control range 90°<)

Inch	DN [mm]	d [mm]	PN	EPDM Code	FPM Code	
2	50	63	10	199 242 282	199 242 302	
2 ½	65	75	10	199 242 283	199 242 303	
3	80	90	10	199 242 284	199 242 304	
4	100	110	10	199 242 285	199 242 305	
5	125	140	10	199 242 286	199 242 306	
6	150	160	10	199 242 287	199 242 307	
8	200	225	10	199 242 288	199 242 308	



PROGEF Standard Lugstyle butterfly valve type 242 FO (Fail safe to open) Without manual override

Model:

- Material: PP-H
- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Control range 90°<)

Inch	DN [mm]	d [mm]	PN	EPDM Code	FPM Code	
2	50	63	10	199 242 322	199 242 342	
2 ½	65	75	10	199 242 323	199 242 343	
3	80	90	10	199 242 324	199 242 344	
4	100	110	10	199 242 325	199 242 345	
5	125	140	10	199 242 326	199 242 346	
6	150	160	10	199 242 327	199 242 347	
8	200	225	10	199 242 328	199 242 348	