


# AN COMPRESSION FITTINGS

## 90° Elbow with threaded female offtake



- (\*) with stainless steel reinforcement ring **AISI430**
- active sealing system (with thrust ring); double lip gasket;
- installation without disassembling
- suitable for PE and PEX-a pipes
- water PN10
- material: PP
- gasket: NBR quality for drinkable water
- female thread: ISO 7 (parallel)
- colour: black




d [mm]	Rp [inch]	PN	Code	SP	GP	kg	d1 [mm]	d2 [mm]	L [mm]	L1 [mm]	L2 [mm]	H [mm]
16	1/2	10	<b>700 627 000</b>	25	200	0.061	22	46	71	58	18	50
16	3/4	10	<b>700 627 001</b>	25	200	0.063	22	46	71	58	18	50
20	1/2	10	<b>700 627 002</b>	25	200	0.059	22	46	71	58	18	50
20	3/4	10	<b>700 627 003</b>	25	200	0.062	22	46	71	58	18	50
25	1/2	10	<b>700 627 004</b>	25	150	0.089	28	54	77	63	21	53
25	3/4	10	<b>700 627 005</b>	25	150	0.081	28	54	77	63	21	53
25	1	10	<b>700 627 006</b>	25	125	0.086	28	54	77	63	21	60
32	1/2	10	<b>700 627 007</b>	25	100	0.145	34	64	88	68	19	60
32	3/4	10	<b>700 627 008</b>	25	100	0.138	34	64	85	68	19	60
32	1	10	<b>700 627 009</b>	25	100	0.125	34	64	85	68	19	60
* 40	1 1/4	10	<b>700 627 010</b>	70	0	0.223	42	77	105	78	30	54
* 50	1 1/2	10	<b>700 627 011</b>	50	0	0.279	52	88	105	76	27	55
* 50	2	10	<b>700 627 012</b>	30	0	0.450	53	93	130	97	28	75
* 63	2	10	<b>700 627 013</b>	25	0	0.502	66	106	130	95	29	70
* 75	2 1/2	10	<b>700 627 014</b>	12	0	1.036	78	134	178	129	48	75
* 90	3	10	<b>700 627 015</b>	7	0	1.484	93	156	227	155	62	100
* 110	4	10	<b>700 627 016</b>	4	0	1.903	114	177	247	159	57	116

## 90° Tee with threaded male offtake



- active sealing system (with thrust ring); double lip gasket;
- installation without disassembling
- suitable for PE and PEX-a pipes
- water PN10
- material: PP
- gasket: NBR quality for drinkable water
- male thread: ISO 7 (conical)
- colour: black



d [mm]	R [inch]	PN	Code	SP	GP	kg	d1 [mm]	d2 [mm]	L [mm]	L1 [mm]	L2 [mm]	H [mm]
16	1/2	10	<b>700 627 017</b>	25	125	0.097	22	44	134	53	28	50
16	3/4	10	<b>700 627 018</b>	25	125	0.097	22	44	134	53	28	50
20	1/2	10	<b>700 627 019</b>	25	125	0.089	22	44	137	54	26	50
20	3/4	10	<b>700 627 020</b>	25	125	0.095	22	46	143	58	18	50
25	1/2	10	<b>700 627 021</b>	25	75	0.131	28	54	153	59	17	52
25	3/4	10	<b>700 627 023</b>	25	75	0.130	28	54	153	59	17	52
25	1	10	<b>700 627 022</b>	25	75	0.129	28	54	153	59	17	52
32	3/4	10	<b>700 627 024</b>	15	45	0.206	34	64	175	59	19	58
32	1	10	<b>700 627 025</b>	15	45	0.201	34	60	166	63	27	59
40	1 1/4	10	<b>700 627 026</b>	35	0	0.349	42	77	210	78	30	73
50	1 1/2	10	<b>700 627 027</b>	25	0	0.425	52	88	210	76	27	76
63	2	10	<b>700 627 028</b>	16	0	0.675	66	106	262	95	29	82