

60 050 600



Extension spindle for tapping valves and service valves Rigid

- PE-casing with anti-sand cap
- PE-sleeve, suitable for tapping valve and service valve (insert needed)
- Square bar steel, hot-dip galvanized
- Clip-pin from stainless steel 1.4301
- Bush CI40 with slot and clip-pin (tool-free connection)

Pipe cover [m]	Code	kg	L [mm]	
0.75	160 050 620	1.200	490	
1.00	160 050 621	1.592	740	
1.25	160 050 622	2.031	990	
1.50	160 050 623	2.448	1180	

PF 2 51 313 017

60 050 500



Extension spindle for tapping valve and service valve Telescopic

- Continuously adjustable and self-supporting
- Pullout- and dirt-safe
- Rod hot-dip galvanized
- PE-casing and PE-centering cap with gasket
- Clip-pin from stainless steel 1.4301
- Bush CI40 with slot and clip-pin (tool-free connection)
- PE-sleeve, suitable for tapping valve and service valve (insert needed)

Pipe cover [m]	Code	kg	L [mm]	L1 [mm]	
0.75-1.05	160 050 520	2.031	450	700	
1.00-1.50	160 050 521	2.500	760	1300	
1.30-1.90	160 050 522	2.700	930	1550	
1.70-2.70	160 050 523	2.000	1300	2350	

PF 2 51 313 017