

PVC-U metric



Lugstyle butterfly valve type 568 PVC-U Bare shaft

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Interface F07 according to DIN/ISO 5211

Inch	DN [mm]	PN	EPDM Code	FPM Code
2	50	10	161 568 902	161 568 922
2 ½	65	10	161 568 903	161 568 923
3	80	10	161 568 904	161 568 924
4	100	10	161 568 905	161 568 925
5	125	10	161 568 906	161 568 926
6	150	10	161 568 907	161 568 927
8	200	10	161 568 908	161 568 928



Lugstyle butterfly valve type 142 PVC-U 100-230V Without manual override

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Voltage 100-230 V, 50-60 Hz
- Control time 15 s/90°<) EA31
- Control time 25s/90°<) EA42
- Control range 90°<)
- Actuator with integrated emergency manual override standard

Inch	DN [mm]	PN	EPDM Code	FPM Code
2	50	10	199 142 042	199 142 062
2 ½	65	10	199 142 043	199 142 063
3	80	10	199 142 044	199 142 064
4	100	10	199 142 045	199 142 065
5	125	10	199 142 046	199 142 066
6	150	10	199 142 047	199 142 067
8	200	10	199 142 048	199 142 068



Lugstyle butterfly valve type 142 PVC-U 100-230V With manual override

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Voltage 100-230 V, 50-60 Hz
- Control time 15 s/90°<) EA31
- Control time 25s/90°<) EA42
- Control range 90°<)
- Actuator with integrated emergency manual override standard

Inch	DN [mm]	PN	EPDM Code	FPM Code
2	50	10	199 142 002	199 142 022
2 ½	65	10	199 142 003	199 142 023
3	80	10	199 142 004	199 142 024
4	100	10	199 142 005	199 142 025
5	125	10	199 142 006	199 142 026
6	150	10	199 142 007	199 142 027
8	200	10	199 142 008	199 142 028