

# PVC-U metric



## Lugstyle butterfly valve type 568 PVC-U Bare shaft

### Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Interface F07 according to DIN/ISO 5211

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	161 568 802	161 568 822
75	65	2 ½	10	161 568 803	161 568 823
90	80	3	10	161 568 804	161 568 824
110	100	4	10	161 568 805	161 568 825
140	125	5	10	161 568 806	161 568 826
160	150	6	10	161 568 807	161 568 827
225	200	8	10	161 568 808	161 568 828



## Lugstyle butterfly valve type 241 PVC-U FC (Fail safe to close) Without manual override

### Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Control range 90°<

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	199 241 002	199 241 022
75	65	2 ½	10	199 241 003	199 241 023
90	80	3	10	199 241 004	199 241 024
110	100	4	10	199 241 005	199 241 025
140	125	5	10	199 241 006	199 241 026
160	150	6	10	199 241 007	199 241 027
225	200	8	10	199 241 008	199 241 028



## Lugstyle butterfly valve type 241 PVC-U FO (Fail safe to open) Without manual override

### Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Control range 90°<

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	199 241 042	199 241 062
75	65	2 ½	10	199 241 043	199 241 063
90	80	3	10	199 241 044	199 241 064
110	100	4	10	199 241 045	199 241 065
140	125	5	10	199 241 046	199 241 066
160	150	6	10	199 241 047	199 241 067
225	200	8	10	199 241 048	199 241 068