

PVC-U metric

Solenoid valves



Solenoid valve type 157 PVC-U
Nominal voltage 230V 50Hz ±10%
Function A straight-through valve 2/2 ways
With threaded sockets parallel female thread Rp

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	Inch	PN [bar]	EPDM Code	FPM Code	
4	G3/8	0.0 - 4.0	199 157 007	199 157 002	
6	G3/8	0.0 - 2.0	199 157 008	199 157 003	
8	G3/8	0.0 - 1.0	199 157 009	199 157 004	



Solenoid valve type 157 PVC-U
Nominal voltage 230V 50Hz ±10%
Function B straight-through valve 2/2 ways
With threaded sockets parallel female thread Rp

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	Inch	PN [bar]	EPDM Code	FPM Code	
4	G3/8	0.0 - 4.0	199 157 027	199 157 022	
6	G3/8	0.0 - 2.0	199 157 028	199 157 023	
8	G3/8	0.0 - 1.0	199 157 029	199 157 024	



Solenoid valve type 157 PVC-U
Nominal voltage 24V DC *24V AC/DC
Function A straight-through valve 2/2 ways
With threaded sockets parallel female thread Rp

- With manual override
- Electrical connection: cable plug
- Protection class IP 65

DN [mm]	Inch	PN [bar]	EPDM Code	FPM Code	
4	G3/8	0.0 - 4.0	199 157 627	199 157 622	
6	G3/8	0.0 - 2.0	199 157 628	199 157 623	
* 8	G3/8	0.0 - 1.0	199 157 629	199 157 624	