

## ABS metric



### Lugstyle butterfly valve type 141 ABS 24V Without manual override

**Model:**

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Voltage 24 V AC/DC
- Control time 15 s/90°<) EA31
- Control time 25s/90°<) EA42
- Control range 90°<)
- Actuator with integrated emergency manual override standard

d [mm]	DN [mm]	PN	EPDM Code
63	50	10	<b>199 141 542</b>
75	65	10	<b>199 141 543</b>
90	80	10	<b>199 141 544</b>
110	100	10	<b>199 141 545</b>
140	125	10	<b>199 141 546</b>
160	150	10	<b>199 141 547</b>
225	200	10	<b>199 141 548</b>



### Lugstyle butterfly valve type 141 ABS 24V With manual override

**Model:**

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Voltage 24 V AC/DC
- Control time 15 s/90°<) EA31
- Control time 25s/90°<) EA42
- Control range 90°<)
- Actuator with integrated emergency manual override standard

d [mm]	DN [mm]	PN	EPDM Code
63	50	10	<b>199 141 522</b>
75	65	10	<b>199 141 523</b>
90	80	10	<b>199 141 524</b>
110	100	10	<b>199 141 525</b>
140	125	10	<b>199 141 526</b>
160	150	10	<b>199 141 527</b>
225	200	10	<b>199 141 528</b>