

PROGEF Standard metric



PROGEF Standard Lugstyle butterfly valve type 568 Bare shaft

Model:

- Material: PP-H
- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Interface F07 according to DIN/ISO 5211

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	167 568 802	167 568 822
75	65	2 ½	10	167 568 803	167 568 823
90	80	3	10	167 568 804	167 568 824
110	100	4	10	167 568 805	167 568 825
140	125	5	10	167 568 806	167 568 826
160	150	6	10	167 568 807	167 568 827
225	200	8	10	167 568 808	167 568 828



PROGEF Standard Lugstyle butterfly valve type 241 FC (Fail safe to close) Without manual override

Model:

- Material: PP-H
- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Control range 90°<

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	199 241 282	199 241 302
75	65	2 ½	10	199 241 283	199 241 303
90	80	3	10	199 241 284	199 241 304
110	100	4	10	199 241 285	199 241 305
140	125	5	10	199 241 286	199 241 306
160	150	6	10	199 241 287	199 241 307
225	200	8	10	199 241 288	199 241 308



PROGEF Standard Lugstyle butterfly valve type 241 FO (Fail safe to open) Without manual override

Model:

- Material: PP-H
- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Control range 90°<

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	199 241 322	199 241 342
75	65	2 ½	10	199 241 323	199 241 343
90	80	3	10	199 241 324	199 241 344
110	100	4	10	199 241 325	199 241 345
140	125	5	10	199 241 326	199 241 346
160	150	6	10	199 241 327	199 241 347
225	200	8	10	199 241 328	199 241 348