

PVC-U metric



Lugstyle butterfly valve type 568 PVC-U Bare shaft

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Interface F07 according to DIN/ISO 5211

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	161 568 802	161 568 822
75	65	2 ½	10	161 568 803	161 568 823
90	80	3	10	161 568 804	161 568 824
110	100	4	10	161 568 805	161 568 825
140	125	5	10	161 568 806	161 568 826
160	150	6	10	161 568 807	161 568 827
225	200	8	10	161 568 808	161 568 828



Lugstyle butterfly valve type 141 PVC-U 100-230V Without manual override

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Voltage 100-230 V, 50-60 Hz
- Control time 15 s/90°<) EA31
- Control time 25s/90°<) EA42
- Control range 90°<)
- Actuator with integrated emergency manual override standard

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	199 141 042	199 141 062
75	65	2 ½	10	199 141 043	199 141 063
90	80	3	10	199 141 044	199 141 064
110	100	4	10	199 141 045	199 141 065
140	125	5	10	199 141 046	199 141 066
160	150	6	10	199 141 047	199 141 067
225	200	8	10	199 141 048	199 141 068



Lugstyle butterfly valve type 141 PVC-U 100-230V With manual override

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Voltage 100-230 V, 50-60 Hz
- Control time 15 s/90°<) EA31
- Control time 25s/90°<) EA42
- Control range 90°<)
- Actuator with integrated emergency manual override standard

d [mm]	DN [mm]	Inch	PN	EPDM Code	FPM Code
63	50	2	10	199 141 002	199 141 022
75	65	2 ½	10	199 141 003	199 141 023
90	80	3	10	199 141 004	199 141 024
110	100	4	10	199 141 005	199 141 025
140	125	5	10	199 141 006	199 141 026
160	150	6	10	199 141 007	199 141 027
225	200	8	10	199 141 008	199 141 028