

ABS metric



Lugstyle butterfly valve type 568 ABS Bare shaft

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Interface F07 according to DIN/ISO 5211

d [mm]	DN [mm]	PN	EPDM Code
63	50	10	169 568 802
75	65	10	169 568 803
90	80	10	169 568 804
110	100	10	169 568 805
140	125	10	169 568 806
160	150	10	169 568 807
225	200	10	169 568 808



Lugstyle butterfly valve type 241 ABS FC (Fail safe to close) Without manual override

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Control range 90°<

d [mm]	DN [mm]	PN	EPDM Code
63	50	10	199 241 402
75	65	10	199 241 403
90	80	10	199 241 404
110	100	10	199 241 405
140	125	10	199 241 406
160	150	10	199 241 407
225	200	10	199 241 408



Lugstyle butterfly valve type 241 ABS FO (Fail safe to open) Without manual override

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752
- Control range 90°<

d [mm]	DN [mm]	PN	EPDM Code
63	50	10	199 241 422
75	65	10	199 241 423
90	80	10	199 241 424
110	100	10	199 241 425
140	125	10	199 241 426
160	150	10	199 241 427
225	200	10	199 241 428