


POLY16 Plus COMPRESSION FITTINGS


Male adaptor



- active sealing system (with thrust ring); d16-63 double lip gasket; d75-110 spring gasket
- installation without disassembling
- suitable for PE and PEX-a pipes
- water PN16
- material: PP
- gasket: NBR quality for drinkable water
- male thread: ISO 7 (conical)
- colour: blue-black

d [mm]	R [inch]	PN	Code	SP	GP	kg	d1 [mm]	d2 [mm]	L [mm]	L1 [mm]	L2 [mm]
16	1/2	16	727 926 329	25	350	0.045	22	46	76	20	58
16	3/4	16	727 926 330	25	325	0.047	22	46	76	20	58
20	1/2	16	727 926 306	25	350	0.043	22	46	76	16	56
20	3/4	16	727 926 333	25	325	0.045	22	46	77	15	55
20	1	16	727 926 332	25	300	0.049	22	46	79	15	55
25	1/2	16	727 926 337	25	200	0.067	28	57	80	18	62
25	3/4	16	727 926 307	25	200	0.068	28	57	82	18	62
25	1	16	727 926 336	25	200	0.070	28	57	86	18	64
32	3/4	16	727 926 341	25	125	0.103	34	67	89	20	68
32	1	16	727 926 308	25	125	0.105	34	67	92	20	68
32	1 1/4	16	727 926 340	25	125	0.107	34	67	94	20	70
32	1 1/2	16	727 926 339	25	125	0.108	34	67	93	20	68
40	1	16	727 926 346	70	0	0.207	44	82	113	28	87
40	1 1/4	16	727 926 309	70	0	0.208	44	82	115	28	87
40	1 1/2	16	727 926 345	70	0	0.212	44	82	115	27	87
40	2	16	727 926 347	60	0	0.219	44	82	115	27	87
50	1	16	727 926 353	40	0	0.278	54	93	125	30	99
50	1 1/4	16	727 926 352	40	0	0.281	54	93	127	30	99
50	1 1/2	16	727 926 310	40	0	0.283	54	93	126	30	99
50	2	16	727 926 351	40	0	0.291	54	93	132	30	99
63	1 1/2	16	727 926 358	20	0	0.563	65	117	154	41	119
63	2	16	727 926 311	20	0	0.568	65	117	156	41	119
63	2 1/2	16	727 926 357	20	0	0.579	65	117	160	41	119
75	2	16	727 926 364	18	0	0.820	77	134	177	56	138
75	2 1/2	16	727 926 312	18	0	0.823	77	134	178	56	134
75	3	16	727 926 363	18	0	0.848	77	134	178	56	136
90	2	16	727 926 371	8	0	1.390	93	160	205	68	168
90	2 1/2	16	727 926 372	8	0	1.398	93	160	210	68	168
90	3	16	727 926 313	8	0	1.414	93	160	210	68	168
90	4	16	727 926 369	8	0	1.474	93	160	216	68	168
110	3	16	727 926 376	6	0	1.865	113	181	226	71	178
110	4	16	727 926 314	6	0	1.908	113	181	231	71	178

Flanged joint with metal flange



- active sealing system (with thrust ring); d16-63 double lip gasket; d75-110 spring gasket
- installation without disassembling
- suitable for PE and PEX-a pipes
- water PN16
- material: PP
- gasket: NBR quality for drinkable water
- flange: steel
- colour: blue-black

d [mm]	DN [inch]	DN [mm]	PN	Code	SP	GP	kg
50	1 1/2	40	16	727 706 350	16	0	1.291
50	2	50	16	727 706 351	16	0	1.241
63	2	50	16	727 706 311	12	0	1.527
63	2 1/2	65	16	727 706 357	12	0	1.823
75	2 1/2	65	16	727 706 312	8	0	1.945
75	3	80	16	727 706 363	6	0	2.138