

ABS metric



Lugstyle butterfly valve type 568 ABS Bare shaft

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Interface F07 according to DIN/ISO 5211

Inch	d [mm]	DN [mm]	PN	EPDM Code
2	63	50	10	169 568 902
2 ½	75	65	10	169 568 903
3	90	80	10	169 568 904
4	110	100	10	169 568 905
5	140	125	10	169 568 906
6	160	150	10	169 568 907
8	225	200	10	169 568 908



Lugstyle butterfly valve type 242 ABS FC (Fail safe to close) Without manual override

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Control range 90°<

Inch	DN [mm]	d [mm]	PN	EPDM Code
2	50	63	10	199 242 402
2 ½	65	75	10	199 242 403
3	80	90	10	199 242 404
4	100	110	10	199 242 405
5	125	140	10	199 242 406
6	150	160	10	199 242 407
8	200	225	10	199 242 408



Lugstyle butterfly valve type 242 ABS FO (Fail safe to open) Without manual override

Model:

- Outer body in GGG-40.3 epoxy-coated
- Connecting dimension ANSI/ASME B 16.5 Class 150
- Overall length according to EN 558, ISO 5752
- Control range 90°<

Inch	DN [mm]	d [mm]	PN	EPDM Code
2	50	63	10	199 242 422
2 ½	65	75	10	199 242 423
3	80	90	10	199 242 424
4	100	110	10	199 242 425
5	125	140	10	199 242 426
6	150	160	10	199 242 427
8	200	225	10	199 242 428