

Snorkel Monitor

Models in this configuration feature a 180-degree vertical travel that is ideal for tank cleaning and any other washdown applications. Like all monitors from Fire Pro, heavy-duty construction and red epoxy finish stand up to the rigorous use found in municipal and industrial environments.

Standard Features:

- 1 1/2" (38mm) & 2 1/2" (64mm) steel waterway
- Type 304 stainless steel swivels
- 360° continuous horizontal travel
- 180° vertical travel
- 125 & 750 GPM (473 & 2839 LPM)

OPTIONS:

Stainless steel waterway
 Other colors available
 Nozzles sold separately



FP3SN-750

Snorkel

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)
FP1SN-125	18 (457)	11 (279)	20 (9)	1-1/2 (38)	1-1/2 (38) 150# RF flange	125 (473)
FP1MSN-125	18 (457)	11 (279)	20 (9)	1-1/2 (38)	1-1/2 (38) 150# RF flange	125 (473)
FP1FSN-125	18 (457)	11 (279)	20 (9)	1-1/2 (38)	1-1/2 (38) 150# RF flange	125 (473)
FP2SN-750	22 (559)	16 (406)	52 (24)	2-1/2 (64)	2-1/2 (64) 150# RF flange	750 (2839)
FP3SN-750	22 (559)	16 (406)	52 (24)	2-1/2 (64)	3 (76) 150# RF flange	750 (2839)
FP4SN-750	22 (559)	16 (406)	52 (24)	2-1/2 (64)	4 (102) 150# RF flange	750 (2839)
FP6SN-750	22 (559)	16 (406)	52 (24)	2-1/2 (64)	6 (152) 150# RF flange	750 (2839)