

FP-3523



FP-3523 - Steering Wheel Control "C" clamp adjustable control, black vinyl dipped with stainless steel fasteners. Steering wheel can be positioned for personal ease of operation or to accommodate low overhead doors for clearance when monitor is mounted on an apparatus. Outside diameter is 13" (330mm).

FP-3525




FP-3525 - Mini Stream Shaper lightweight aluminum or brass body with hard anodized finish and replaceable Delrin "Honeycomb" grid straightens steam minimizing water turbulence, resulting in improved, effective distance and overall reach. 1-1/2" (38mm) (3515) or 2-1/2" (64mm) (3525) NH female inlet x 2-1/2" (64mm) NH outlet.



FP-3526

FP-3526 - Pressure Gauge is stainless steel and liquid filled with a protective cover. 0-300# mounted on monitors at the base of the nozzle so that operator can insure proper pressure ranges for maximum, effective operation of both straight bore and combination fog/straight stream nozzles.



FP-3527

FP-3527 - Drain Outlet brass construction 1/4" (6mm) NPT male base with drain cock. Idea for pressure relief when used with automatic nozzle or in cold climates where water removal is necessary.

FP-3528 - Butterfly Valve 2-1/2" (64mm), 3" (76mm) or 4" (102mm) with aluminum bronzed wafer mounted in a neoprene seat. Cast steel body and handle with locking plate.

FP-3529 - Hydrant Mount 2-1/2" (64mm) or 3" (76mm) NPT male discharge thread with 2-1/2" (64mm) N.H. swivel inlet. "C" clamp hydrant bracket support arms are designed to fit on virtually any hydrant style. Red epoxy finish.

FP-3530 - Hydrant Mount with 2-1/2" (64mm) or 3" (76mm) 150# ASA raised face flange discharge with 2-1/2" (64mm) NH female swivel inlet. Flange outlet ideal to mount flange base monitor on butterfly valve.

FPHM-2 - Hydrant Mount only with two leg 2-1/2" (64mm) swivel inlet, 2-1/2" (64mm) flange or NPT outlet.

FP-3528



FP-3530



FPHM-2M

shown on hydrant
PF350 monitor not included

