



## Variable area flow meter type 350 Float in PVDF without magnet With solvent cement sockets PVC-U metric



- \* PVC-U transparent >DN40 available from Sept. 2009

Scale range [l/h]	d [mm]	DN [mm]	Taper tube in PVC-U transp. O-rings in EPDM Code	Taper tube in Polyamid O- rings in EPDM Code	Taper tube in Polysulfone O- rings in EPDM Code
50 - 500	32	25	<b>198 350 000</b>	<b>198 350 020</b>	<b>198 350 040</b>
100 - 1000	32	25	<b>198 350 001</b>	<b>198 350 021</b>	<b>198 350 041</b>
150 - 1500	40	32	<b>198 350 002</b>	<b>198 350 022</b>	<b>198 350 042</b>
250 - 2500	40	32	<b>198 350 003</b>	<b>198 350 023</b>	<b>198 350 043</b>
200 - 2000	50	40	<b>198 350 004</b>	<b>198 350 024</b>	<b>198 350 044</b>
300 - 3000	50	40	<b>198 350 005</b>	<b>198 350 025</b>	<b>198 350 045</b>
600 - 6000	50	40	<b>198 350 006</b>	<b>198 350 026</b>	<b>198 350 046</b>
600 - 6000	63	50	<b>198350007*</b>	<b>198 350 027</b>	<b>198 350 047</b>
1000 - 10000	63	50	<b>198350008*</b>	<b>198 350 028</b>	<b>198 350 048</b>
1500 - 15000	63	50	<b>198350009*</b>	<b>198 350 029</b>	<b>198 350 049</b>
2000 - 20000	75	65	<b>198350010*</b>	<b>198 350 030</b>	<b>198 350 050</b>
3000 - 30000	75	65	<b>198350011*</b>	<b>198 350 031</b>	<b>198 350 051</b>
8000 - 60000	75	65	<b>198350012*</b>	<b>198 350 032</b>	<b>198 350 052</b>

Scale range [l/h]	D [mm]	L [mm]	L1 [mm]	L2 [mm]	G [inch]
50 - 500	58	400	356	350	1 ½
100 - 1000	58	400	356	350	1 ½
150 - 1500	72	408	356	350	2
250 - 2500	72	408	356	350	2
200 - 2000	83	418	356	350	2 ¼
300 - 3000	83	418	356	350	2 ¼
600 - 6000	83	418	356	350	2 ¼
600 - 6000	101	432	356	350	2 ¾
1000 - 10000	101	432	356	350	2 ¾
1500 - 15000	101	432	356	350	2 ¾
2000 - 20000	135	444	356	350	3 ½
3000 - 30000	135	444	356	350	3 ½
8000 - 60000	135	444	356	350	3 ½