

## SERIES 34 PNEUMATIC ACTUATOR



### Features

- Compact Scotch-Yoke design
- Baked epoxy coating
- Minimum air consumption
- Adjustable speed control
- Single external air and electrical connections
- Fail-safe spring return option
- Built-in solenoid air pilot
- High temperature option

### Torque Range

- Up to 1000 in-lbs @ 100 psi input

### Temperature Range

- -25 F to 160 F, Optional to 250 F

### Supply Voltage

- 24, 120, 240, 480 VAC; 12, 24VDC

### Standards

- Type 1, 4, 4x
- Class 1, Div 1, Groups A, B, C, D

### Applications

- Industrial Qtr-Turn valve automation
- Automotive, OEM, Chemical & Water

Get more information:

Product catalog:  
WCENBR1004

IOM  
WCAIM2008

See page 2.

## SERIES 39 PNEUMATIC ACTUATOR



### Features

- High Performance, High Cycle Design
- Two-Year warranty
- Twin piston, double rack & pinion
- Extruded, anodized aluminum body
- NAMUR, ISO mounting
- Polished stainless steel guide rods
- Multi-spring force transfer
- Dual male output shafts
- End cap air supply ports
- End mount solenoid/switch accessories

### Torque Range

- Up to 60,000 in-lbs @ 120 psi input

### Temperature Range

- -40 F to 212 F; (high temp option 300F)

### Pressure Range

- 30-120psi DA, 40-120psi SR

### Standards

- Type 1, 4, 4x
- Class 1, Div 1, Groups A, B, C, D

### Applications

- Chemical, Petrochemical & Refining,
- Power, Oil & Gas, Food & Beverage

Get more information:

Product catalog:  
WCABR1003

IOM  
WCAIM2036

See page 2.

## ACCESS ACTUATOR PNEUMATIC ACTUATOR with PROCESS INTERFACE



### Features

- Integral solenoid & position switch
- Single electrical connection
- High flow spool valve
- Manual override and speed control
- No mounting brackets
- Diagnostic LED circuit board
- Digital Fieldbus networks

### Torque Range

- Up to 60,000 in-lbs

### Enclosure

- Type 4, 4X; U.L.; CSA approved
- Class 1, Div 1, Groups B, C, D
- Intrinsically Safe, NRTL/C approved

### Position Switch

- SPDT/DPDT, Gold Contact, Proximity

### Temperature Range

- 0 F to 160 F

### Supply Voltage

- 12, 24 VDC, 24, 120, 240 VAC

### Pressure Range

- 40 to 120 psi

### Standards

- 4, 4x, 7, 9 and 12

### Applications

- Digital Fieldbus Networks, Chemical,
- Petrochemical & Refining, Oil & Gas,
- Food & Beverage, Pharmaceutical

Get more information:

Product catalog:  
WCABR1024

IOM  
WCAIM2027  
WCAIM2028  
WCAIM2023  
WCAIM2032

See page 2.