

Portable Monitors

Portable monitors, rated at 750 or 1,200 gpm, are versatile performers, either on the apparatus or in a portable mode. They feature quick "long handle" swivel detachment from the apparatus for mounting on the portable base and two "slip in" stabilizing legs with no-skid neoprene pads. Furnished complete with truck mount adapter and 500A aluminum Master Stream nozzle, with optional 750 or 1,200 GPM master stream available. Spring loaded locking knobs ensure safe stream available. Available in standard and short radius models.

Standard Features:

- Field-proven reliability
- Highest flows available for portable monitors
- Portable or fixed operation
- Single waterway – less friction loss
- "Long handle" swivel detachment
- Short radius (long radius also available)
- Stabilizing legs with no-skid neoprene pads
- Detachable truck mount (1 1/2", 38mm)
- 125-350, 750 & 1,200 GPM (473-1325, 2839, 4542 LPM)
- 1-1/2", 2-1/2", 3" sizes (38, 64, 76mm)



125 GPM

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)
FPPM-125	11 (279)	24 (610)	45 (20)	1-1/2 (38) flange	1-1/2 (38)	125-350 (473-1325)

750 GPM

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)
FPPMSR-750	11"	24 (610)	45 (20)	2-1/2 (64) truck mount w/ adapter, portable base, legs & 500A nozzle	2-1/2 (64)	750 (2839)
FPPM-750M	16"	28 (711)	55 (25)	2-1/2 (64) monitor only with legs	2-1/2 (64)	750 (2839)

1200 GPM

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)
FPPMSR-1200	24 (610)	28 (711)	65 (30)	3 (76) truck mount w/ adapter, portable base, legs & 500A nozzle	3 (76)	1,200 (4542)
FPPM-1200M	24 (610)	36"	85 (39)	3 (76) monitor only with legs	2-1/2 (64)	1,200 (4542)
FPPM-LAC				3 (76) polished stainless steel w/ parallel control handles	2-1/2 (64)	1,200 (4542)