

Smooth Bore Nozzles

Smooth bore nozzles convey water at maximum reach and with the best overall straight stream quality. They are constructed of anodized aluminum, and coated with a durable Teflon protective coating. Smooth bore nozzles from Fire Pro are a reliable and economical choice.



FP10425-13

FP10425-11

FP10425-9



FP-3120

1-1/2" (38cm) aluminum straight bore nozzle with 1" (25cm) orifice
Hard anodized grey finish

Smooth Bore

Model	Length (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	GPM (GPM/LPM)
FP10425-1	13 (330)		1/2 (13)	75 (284)
FP10425-2	13 (330)		5/8 (16)	117 (443)
FP10425-3	13 (330)		3/4 (19)	168 (636)
FP10425-4	13 (330)		7/8 (22)	229 (867)
FP10425-5	13 (330)		1 (25)	299 (1132)
FP10425-6	13 (330)		1-1/8 (29)	378 (1431)
FP10425-7	13 (330)		1-1/4 (32)	467 (1768)
FP10425-8	13 (330)		1-3/8 (35)	565 (2139)
FP10425-9	13 (330)		1-1/2 (38)	673 (2548)
FP10425-10	13 (330)		1-5/8 (41)	789 (2987)
FP10425-11	13 (330)		1-3/4 (44)	915 (3464)
FP10425-12	13 (330)		1-7/8 (48)	1,051 (3978)
FP10425-13	13 (330)		2 (51)	1,195 (4524)
FP-3110	4 1/2 (114)	2 (0.9)	1 (25)	3/8" (25cm) orifice
FP-3120	5 (127)	11-1/5 (5)	1-1/2 (38)	1-3/8" (35cm) orifice
FP-3205	9 (229)	3-1/5 (1.5)	2-1/2 (64)	1-1/2" (38cm) orifice
FP-3210	10 (254)	4 (2)	2-1/2 (64)	1-1/2" (38cm) orifice

Smooth Bore - Brass

Cast brass straight bore tip with 2-1/2" (64cm) NH female base with various orifices

Model	Length (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Orifice (in/mm)
FP-3200-1	10 (254)	4 (2)	2-1/2 (64)	1 (25)
FP-3200-1-1/4	10 (254)	4 (2)	2-1/2 (64)	1-1/4 (32)
FP-3200-1-3/8	10 (254)	4 (2)	2-1/2 (64)	1-3/8 (35)
FP-3200-1-1/2	10 (254)	4 (2)	2-1/2 (64)	1-1/2 (38)
FP-3200-1-3/4	10 (254)	4 (2)	2-1/2 (64)	1-3/4 (44)
FP-3200-1-7/8	10 (254)	4 (2)	2-1/2 (64)	1-7/8 (48)
FP-3200-2	10 (254)	4 (2)	2-1/2 (64)	2 (51)



FP-3200