

Trailers

2-wheel trailer portable monitor rated at either 750 or 1,200 GPM (2839 or 4542 LPM). The FP-750C has a full flow 2-1/2" (64mm) waterway with 3" (76mm) manifold and two 2-1/2" (64mm) female swivel inlets with check valves standard. The FP-1200C has a full-flow 3" (76mm) waterway and four 2-1/2" (64mm) female swivel inlets with check valves standard. Both models are furnished with "spring-loaded" wheel locks and low profile tires. 1-7/8" (48mm) ball-type hitch standard. Two racks will carry four 50-foot (15m) lengths of 2-1/2" (64mm) hose. Standard red epoxy finish. Optional additional inlets and butterfly valve.



FP-1200C

Charger

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)
FP-750C	24 (610)	78 (1981)	270 (123)	3 (76) manifold w/ 2 x 2-1/2 (51x64) female swivel	2-1/2 (64)	750 (2839)
FP-1200C	24 (610)	78 (1981)	290 (132)	3 (76) manifold w/ 3 x 3 (76x76) female swivel	3 (76)	1,200 (4542)
FP-2000C	48 (1219)	96 (2438)	320 (145)	6 (152) manifold w/ 2 x 4 (51x102) female swivel	4 (102)	2,000 (7571)

4-wheel portable monitor with full flow 2-1/2" (64mm) waterway designed for one-man operation, with "T" manifold and two 2-1/2" female swivel inlets with check valves standard. Furnished with four wheel locks and "spring-loaded" locking knobs to limit vertical travel to +20° and 40 degrees either side of center horizontal travel for safety. Standard red epoxy finish. Optional additional inlets and hose racks for 2 lengths of 2-1/2" (64mm) fire hose. Length including "T" handle.



FP-750MC

Mini Charger

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)
FP-750MC	24 (610)	56 (1442)	110 (50)	"T" manifold w/ 2 x 2-1/2 (51x64) female swivel	2-1/2 (64)	750 (2839)