

# FIRE DEPT CONNECTION ACCESSORIES

## OPEN SNOOTS

**FUNCTION:** Used to connect fire hose to a standpipe or sprinkler system.

**REGULARLY FURNISHED:** Cast brass connection with size and type of inlet and outlet as selected by Model Number. Polished brass exposed parts.

Female Inlet x Male Outlet

Female Inlet x Male Outlet with Pin Lug Swivel

Double Female with Pin Lug Swivel



**5902-5905**



**5911-5915**



**5922-5925**



Model	NPT Inlet	Hose Outlet	Model	Hose Inlet	NPT Outlet	Model	Type	Hose Inlet	NPT Outlet
5902	2½"/6.4 cm	2½"/6.4 cm	5911	1½"/3.8 cm	1½"/3.8 cm	5922	Hex	2½"/6.4 cm	2½"/6.4 cm
5903	3"/7.6 cm	2½"/6.4 cm	5912	2½"/6.4 cm	2½"/6.4 cm	5923	Hex	2½"/6.4 cm	3"/7.6 cm
5905	3"/7.6 cm	3"/7.6 cm	5913	2½"/6.4 cm	3"/7.6 cm	5925	Hex	3"/7.6 cm	3"/7.6 cm
			5915	3"/7.6 cm	3"/7.6 cm				

**OPTIONAL FINISH:** -D Polished Chrome Plated on Exposed Parts

**SPECIFY:** Thread

## CHECK SNOOTS WITH PIN LUG SWIVEL

**FUNCTION:** Used to connect fire hose on multiple inlet fire dept connections. Acts as a check against an excess backflow of water.

**REGULARLY FURNISHED:** Cast brass connection with size and type of inlet and outlet as selected by Model Number. Polished brass exposed parts.

### SPRING TYPE

### CLAPPER TYPE

Double Female Female Inlet x Male Outlet

Double Female Female Inlet x Male Outlet



**5930-5936**



Model	Female Hose Inlet	NPT Outlet	Model	Female Hose Inlet	NPT Outlet
5930	2½"/6.4 cm	3"/7.6 cm Female	5937	2½"/6.4 cm	3"/7.6 cm Female
5933	3"/7.6 cm	3"/7.6 cm Female	5938	2½"/6.4 cm	3"/7.6 cm Male
5935	2½"/6.4 cm	3"/7.6 cm Male			
5936	3"/7.6 cm	3"/7.6 cm Male			

**OPTIONAL FINISH:** -D Polished Chrome Plated on Exposed Parts

**SPECIFY:** Thread

## PLUGS AND CHAIN

**FUNCTION:** Used on fire dept inlet connections. Discourages entry of foreign matter and protects female threads.

### PIN LUG

### PENTAGONAL HEAD


Cast brass pin lug plug with male hose thread and attached chain. Size as selected by Model Number.

Cast brass pentagonal head plug with male hose thread and attached chain. Size as selected by Model Number.

Model	Size
5941	2½"/6.4 cm
5942	3"/7.6 cm
5943	4"/10.2 cm
5944	4½"/11.4 cm

Model	Size
5945	2½"/6.4 cm
5948	3"/7.6 cm

**SPECIFY:** Thread



**OPTIONAL FINISHES:** -B Polished Brass -C Rough Chrome Plated -D Polished Chrome Plated

## BREAKABLE CAPS

**FUNCTION:** Used on fire dept inlet connections. Discourages entry of foreign matter and protects female threads. Breakable feature allows fast hose hook-up.

**REGULARLY FURNISHED:** Aluminum cover with breakable ears; two eye bolts and nuts for attachment to female pin lug swivel.

Model	Size
5950	2½"/6.4 cm
5953	3"/7.6 cm

**VARIATION:**

-P Red plastic breakable cap 2½"/6.4 cm size  
**OPTIONAL FINISH:** Painted **SPECIFY:** Color



**5950 & 5953**

# FIRE DEPARTMENT CONNECTION ACCESSORIES

POTTER-ROEMER



A Division of Smith Industries, Inc.

## ROUND IDENTIFICATION PLATES

**FUNCTION:** Used to identify and trim exposed fire dept connection installations.

**REGULARLY FURNISHED:** Brass or red finish aluminum plate, size and material as selected by Model Number. Lettering as selected.

Model No.	Pipe Size	Plate Diameter	Material
5962	4	9 <sup>3</sup> / <sub>4</sub>	Brass
	10.2	24.7	
5964	6	12	Brass
	15.2	30.4	

**OPTIONAL FINISHES:** (Brass only)

- B Polished Brass
- D Polished Chrome Plated

**VARIATION:**

- F Sillcock Flange Plate (Brass only)
- E Any engraved lettering

Model No.	Pipe Size	Plate Diameter	Material
5966	4	9 <sup>3</sup> / <sub>4</sub>	Aluminum
	10.2	24.7	
5968	6	12	Aluminum
	15.2	30.4	

**LETTERING AVAILABLE:**

- AUTO SPKR
- STANDPIPE
- DRY STANDPIPE
- AUTO SPKR STANDPIPE
- WALL HYDRANT
- PUMP TEST CONN

**SPECIFY:** Lettering



5962-5968

## RECTANGULAR IDENTIFICATION PLATES

**FUNCTION:** Used with fire dept connections for identification.

**REGULARLY FURNISHED:** 4 x 8" / 10.2 cm x 20.4 cm brass or red finish aluminum plate, material as selected by Model Number. Lettering as selected.

<b>Model</b>	
5970	..... Brass
5975	..... Aluminum

**OPTIONAL FINISHES:** (Brass only)

- B Polished Brass
- D Polished Chrome Plated

**VARIATION:**

- E Any engraved lettering

**SPECIFY:** Lettering

**LETTERING AVAILABLE:**

- NORTH DRY STANDPIPE
- SOUTH DRY STANDPIPE
- EAST DRY STANDPIPE
- WEST DRY STANDPIPE
- ALL DRY STANDPIPE
- STANDPIPE
- DRY STANDPIPE FIRE DEPT CONN
- COMBINATION STANDPIPE
- AUTO SPKR FIRE DEPT CONN
- PUMP TEST CONNECTION
- FIRE DEPARTMENT CONNECTION
- AUTO SPKR STANDPIPE





5970 & 5975

## AUTOMATIC DRAIN DEVICE

**FUNCTION:** Used to drain low point of system between fire dept connection and swing check valve. Seals automatically under pressure. Installed in horizontal position only.

**REGULARLY FURNISHED:** Cast brass angle or straight connection, male NPT both ends. Size and design as selected by Model Number.

Model	Size	Design
5981	..... 1/2" / 1.2 cm	Straight
5982	..... 3/4" / 1.9 cm	Straight
5983	..... 1/2" / 1.2 cm	Angle
5984	..... 3/4" / 1.9 cm	Angle



5981-5984

## SILLCOCK

**FUNCTION:** Used to manually drain low point of system between fire dept connection and swing check valves.

**REGULARLY FURNISHED:** Polished brass flanged sillcock with 3/4" / 1.9 cm female NPT inlet x male GHT; stem shield and removable tee handle key.

**OPTIONAL FINISHES:**

- D Polished Chrome Plated



5990